

src/app/CodeCityViewportContext.tsx

Kind: added · Baseline: 9aadd5eb5604 · Target: NovaDiff · Generated: 2026-05-26T19:25:45.918Z

Overview

A new file `src/app/CodeCityViewportContext.tsx` (added) introduces a React context for the CodeCity viewport state. It exports an interface, a provider component, and a hook to consume the `expanded` flag.

Key changes

- **Imports** – `createContext` and `useContext` from React (R1).
- **State interface** – `export interface CodeCityViewportState { expanded: boolean; }` (R3-R6).
- **Context creation** – `const CodeCityViewportContext = createContext<CodeCityViewportState>({ expanded: false });` (R8-R10).
- **Provider** – `export function CodeCityViewportProvider({ expanded, children })` wraps children with the context value (R12-R23).
- **Hook** – `export function useCodeCityViewport(): CodeCityViewportState` returns `useContext(CodeCityViewportContext)` (R26-R28).

Impact

- Components can read the `expanded` flag without prop drilling.
- The default value `{ expanded: false }` is used when the provider is omitted.
- The API is additive; no existing files are modified.

Risks & follow-ups

- **Provider omission** – `useCodeCityViewport` will return the default state if called outside a provider; verify if this is acceptable.
- **Naming collisions** – Ensure no other context or hook named `CodeCityViewportProvider` / `useCodeCityViewport` exists.
- **Testing** – Add tests to confirm provider propagation and hook consumption.
- **Documentation** – Update component docs to reference the new context API.