

src/app/DocsViewSyncContext.tsx

Kind: modified · Baseline: 9aadd5eb5604 · Target: NovaDiff · Generated: 2026-05-26T19:26:01.687Z

Overview

In `src/app/DocsViewSyncContext.tsx` a new state `cityBuildingId` was added to the `DocsViewSyncState` interface (R16-17) and initialized to `null` (R43). The provider now tracks this ID when a graph node id is unknown or not yet linked.

Key changes

- **Interface** – `cityBuildingId: string | null` (R16-17).
- **State** – `const [cityBuildingId, setCityBuildingId] = useState<string | null>(null);` (R43).
- **Selection logic** –
 - `setSelectionFromGraph` now clears `cityBuildingId` when a node id is present and no longer resets `enteredBuilding` on falsy ids (L49-50 removed, R52-57 added).
 - `setSelectionFromCity` assigns `cityBuildingId = building.id` when a building is supplied and removes the old `building !== undefined` guard (R62-70, R72).
- **Enter/exit/clear helpers** – update `cityBuildingId` (R84, R94, R100).
- **Context value** – includes `cityBuildingId` and its dependency array is updated (R113-128).

Impact

- **Consistency** – a single source of truth for the building id when the graph node is missing.
- **Maintainability** – consumers can rely on `cityBuildingId` without extra logic.
- **Compatibility** – TypeScript will enforce handling of the new field; existing consumers receive an additional property.
- **Performance** – negligible overhead from an extra state setter.

Risks & follow-ups

- **Regression** – components that previously cleared `enteredBuilding` on falsy `nodeId` may behave differently; review related logic.
- **Type safety** – ensure all destructurings import the updated `DocsViewSyncState`.
- **Dependency array** – confirm `cityBuildingId` is listed in `useMemo` dependencies to avoid stale closures.
- **Testing** – add unit tests for `setSelectionFromGraph` and `setSelectionFromCity` to assert the new `cityBuildingId` handling.