

src/components/CodeCityMinimapSlot.tsx

Kind: modified · Baseline: 9aadd5eb5604 · Target: NovaDiff · Generated: 2026-05-26T19:34:32.775Z

Overview

`src/components/CodeCityMinimapSlot.tsx` now registers a listener for the global event `novadiff-code-viewer-open-change`. The handler (`update`) recalculates the minimap insets whenever the code-viewer's open state changes.

Key changes

- **Added listener** (line 72):

```
``ts window.addEventListener("novadiff-code-viewer-open-change", update);
```
- **Removed listener** (line 78):

```
ts window.removeEventListener("novadiff-code-viewer-open-change", update);
```

 - No other imports or logic were modified; the component still relies on `measureCodeCityChromeInsets`, `ResizeObserver`, and `MutationObserver` for layout changes.

Impact

- The component now reacts to the code-viewer's open/close state, which may prevent stale inset values when the viewer toggles.
- The added listener is lightweight, merely scheduling a single `requestAnimationFrame` update.
- Cleanup occurs in the same effect cleanup block, ensuring no lingering listeners after unmount.

Risks & follow-ups

- **Event name mismatch:** Verify that the code-viewer dispatches `novadiff-code-viewer-open-change`.
- **Duplicate listeners:** Ensure that multiple mounts of `CodeCityMinimapSlot` do not accumulate listeners; the cleanup logic should prevent this.
- **Update idempotency:** Confirm that rapid open/close toggles do not cause race conditions or unnecessary re-renders.
- **Testing coverage:** Add unit tests that simulate the event dispatch and assert that `measureCodeCityChromeInsets` is invoked with the correct host element.