

src/components/launch/AppLaunchShell.tsx

Kind: modified · Baseline: 9aadd5eb5604 · Target: NovaDiff · Generated: 2026-05-26T19:42:14.453Z

Overview

`AppLaunchShell` now accepts an optional `shellClassName` prop that appends custom CSS classes to the root `.app-shell` element. The public API and internal class composition have been updated accordingly.

Key changes

- **Interface** (`src/components/launch/AppLaunchShell.tsx` , lines 13-20): added `shellClassName?: string` with a JSDoc comment (R17-18).
- **Function signature** (`AppLaunchShell` lines 21-26): now includes `shellClassName` in the destructured props.
- **Class name construction** (`shellClass` line 70): the array now contains `shellClassName` before joining, replacing the previous two-line definition (L63).
- **Export surface**: the old export (`L19`) was removed; the new export (`R21`) reflects the updated signature.

Impact

- **Backward compatibility**: `shellClassName` is optional, so existing callers remain unaffected.
- **Styling flexibility**: consumers can inject additional classes without modifying the component's source.
- **No runtime logic change**: the launch sequence and phase handling remain identical; only the rendered class list differs.
- **TypeScript enforcement**: the new prop is now typed, and the JSDoc comment aids IDE tooling.

Risks & follow-ups

- **Regression in tests**: snapshot or class-name assertions may need updating.
- **Documentation**: update the component's README/API docs to expose the new prop.
- **Prop collision**: callers should avoid passing a `shellClassName` that conflicts with internal classes.
- **Lint rule**: verify that the added JSDoc comment does not trigger any linting issues.