

src/components/sidebar/useSidebarExpand.ts

Kind: added · Baseline: 9aadd5eb5604 · Target: NovaDiff · Generated: 2026-05-26T19:44:25.230Z

Overview

`src/components/sidebar/useSidebarExpand.ts` was added.

It exports:

- `SidebarTextPhase` ("hidden" | "typing" | "erasing") – R8
- `UseSidebarExpandResult` interface – R10-24
- `useSidebarExpand()` hook – R26-211

The hook manages sidebar expansion, text animation phases, and a promise-based collapse API.

Key changes

- **State & refs** – `pointerInside`, `focusInside`, `panelExpanded`, `textPhase`; refs for timers (`leaveTimerRef`, `eraseTimerRef`, `widthTimerRef`) and flags (`forceCloseRef`, `wantOpenRef`) – R27-38.
- **Timer logic** – uses constants from `./sidebarTiming` (`SIDEBAR_LEAVE_DELAY_MS`, `SIDEBAR_ERASE_FALLBACK_MS`, `SIDEBAR_WIDTH_TRANSITION_MS`) – R3-6.
- **Collapse flow** – `requestCollapse` returns `Promise<void>` that resolves when the panel fully collapses, handling pending waiters and cleanup – R92-122.
- **Event handlers** – `onPointerEnter/Leave`, `onFocusCapture/BlurCapture` guard against forced close and update internal state – R174-194.
- **Effect hooks** – three `useEffect` blocks manage expansion, leave delay, and cleanup on unmount – R132-172.

Impact

- Components can now import `useSidebarExpand` to control sidebar visibility and text animation.
- The hook introduces timer refs; the cleanup effect at R164-172 clears timers on unmount, mitigating stray callbacks.
- No existing component APIs are altered, but any component that previously managed sidebar state should migrate to this hook.

Risks & follow-ups

- **Timer cleanup** – verified that timers are cleared on unmount (R164-172).
- **Race conditions** – `requestCollapse` queues waiters; ensure concurrent calls resolve correctly.
- **Focus handling** – `onBlurCapture` uses `event.relatedTarget`; confirm cross-browser behavior.

- **Type safety** – consuming components must match the `UseSidebarExpandResult` interface; run TypeScript checks to catch mismatches.