

## tests/codeCityLayout.test.ts

Kind: added · Baseline: 9aadd5eb5604 · Target: NovaDiff · Generated: 2026-05-26T19:15:24.063Z

### Overview

A new test file `tests/codeCityLayout.test.ts` was added. It imports `vitest` helpers, `buildCodeCityLayout`, and the `CodeCityModel` type. A helper function `modelWithSrcFilesOnly` (lines 5-7) returns a minimal `CodeCityModel` containing two target-side files ( `src/App.tsx`, `src/util.ts` ) and corresponding file-level symbols (lines 11-38, 40-71).

### Key changes

- **Imports added** (R1-3).
- **Helper function** `modelWithSrcFilesOnly` defined (R5-7) with file and symbol data.
- **Three test cases:**
  1. Builds layout for subsystem `src` when only file symbols exist (lines 76-92).
  2. Handles subsystem paths containing backslashes ( `src\\App.tsx` ) (lines 94-111).
  3. Filters by symbol kind ( `file` ) and change state ( `added` ) (lines 113-158).

### Impact

- Provides a reusable minimal model for testing `buildCodeCityLayout`.
- Adds a factory that can be reused by future tests.
- Tests run locally with `vitest`; no new runtime flags are introduced.

### Risks & follow-ups

- **Regression risk:** any change to `buildCodeCityLayout` that alters symbol handling may break these tests; run the suite after refactors.
- **Path normalization:** ensure the implementation consistently normalizes backslashes; failing tests may surface this.
- **Coverage gap:** the helper covers only target-side files; baseline-side scenarios are not represented.
- **Test isolation:** the helper creates fresh objects each call, so shared state mutation is unlikely.