

electron/git-commit.cjs

Kind: added · Baseline: f7c2bfd81af2 · Target: NovaDiff · Generated: 2026-05-21T10:43:02.263Z

Overview

A new module `electron/git-commit.cjs` is added. It exports a `getCommitDetail` helper that retrieves commit metadata and statistics by invoking Git commands.

Key changes

- Import added at line 3: `const { runGit, tryRunGit } = require("./git-service.cjs");`
- Function `getCommitDetail(repoRoot, hash)` added (lines 1-69):
 - Validates `repoRoot` and `hash` (lines 12-14).
 - Runs `git log -1 <hash>` with a custom format to capture hash, short hash, subject, author, email, date, and parents (lines 16-21).
 - Retrieves the commit body via `git log -1 <hash> --format=%B` (line 23).
 - Calls `git show --stat` (line 28) and parses the summary for `filesChanged`, `insertions`, and `deletions` (lines 30-43). Falls back to line count if the summary is missing (lines 44-46).
- Export added at line 69: `module.exports = { getCommitDetail };`

Impact

- Provides a single public API for commit detail retrieval.
- Throws an error if `repoRoot` or `hash` is missing (lines 12-14).
- Requires three Git commands per call; performance impact is unknown from the diff.

Risks & follow-ups

- Verify that `runGit` / `tryRunGit` in `git-service.cjs` return the expected `stdout` / `ok` flags.
- The regexes used to parse the stat summary may fail on edge cases (e.g., commits with no file changes).
- Test with repositories containing non-ASCII commit messages to confirm UTF-8 handling (unknown from diff).
- Monitor latency in CI pipelines; consider caching or batching if call frequency is high (unknown from diff).