

electron/git-publish.cjs

Kind: modified · Baseline: f7c2bfd81af2 · Target: NovaDiff · Generated: 2026-05-21T10:44:03.464Z

Overview

`electron/git-publish.cjs` now stages a user-supplied list of paths instead of always staging the entire repository. The change adds `stagePaths` to the import from `./git-service.cjs` (line 4) and rewrites the staging logic in `executePublish`.

Key changes

- **Import update** – `stagePaths` is added to the destructured import from `./git-service.cjs` (line 4).
- **Conditional staging** – `stageAll(root)` is replaced by logic that builds `stagePathsList` from `opts.stagePaths` (lines 63-70).
- **Branching** – If `stagePathsList` is non-empty, `stagePaths(root, stagePathsList)` runs; otherwise the original `stageAll(root)` is executed.
- **No other functional changes** – commit, push, and PR creation remain unchanged.

Impact

- **Selective staging** – allows committing only specified files, preventing accidental inclusion of unrelated changes.
- **Maintainability** – staging logic is now isolated; future extensions can modify `stagePaths` without touching `executePublish`.
- **Performance** – staging fewer files can reduce I/O when `opts.stagePaths` is small.
- **Compatibility** – callers that omit `stagePaths` continue to stage all files, preserving current behavior.

Risks & follow-ups

- **Missing `stagePaths` export** – verify that `./git-service.cjs` actually exports `stagePaths`; otherwise the import will fail at runtime.
- **Invalid `opts.stagePaths` values** – if callers pass a non-array (e.g., a string), the code falls back to `stageAll`, which may be unintended. Add validation or document the expected type.
- **Ignored paths** – ensure `stagePaths` respects `.gitignore`; otherwise staged files might be ignored by Git, leading to silent failures.
- **Test coverage** – add unit tests for both branches (with and without `stagePaths`) to confirm behavior and guard against regressions.