

electron/git-service.cjs

Kind: modified · Baseline: f7c2bfd81af2 · Target: NovaDiff · Generated: 2026-05-21T10:44:21.856Z

Overview

Three new helper functions were added to `electron/git-service.cjs` to give callers finer control over staging:

- `stagePaths(repoRoot, paths)` – normalises a list of paths, runs `git add -- <paths>`, and returns `{ staged: N }`.
- `unstagePaths(repoRoot, paths)` – runs `git reset HEAD -- <paths>` and returns `{ unstaged: N }`.
- `stageDistrict(repoRoot, topDir, statusFiles?)` – filters the repository's status files to those under `topDir` (or its sub-directories) and delegates to `stagePaths`.

The module export list was extended (lines 253-255) to expose these utilities.

Key changes

- **`stagePaths`**
 - added at lines 142-149.
- **`unstagePaths`**
 - added at lines 152-159.
- **`stageDistrict`**
 - added at lines 162-169.
- Export list updated to include the three new functions (lines 253-255).
- No other logic was modified.

Impact

- **API surface*
 - callers can now stage or unstage specific files or a whole directory without affecting the rest of the working tree.
- **Implementation*
 - each helper invokes a single `runGit` call, so the runtime cost is minimal compared to existing helpers.

- **Compatibility*
- – existing consumers of `stageAll`, `commit`, `push`, etc. remain unchanged.

Risks & follow-ups

- The behavior of `stageDistrict` when `topDir` is empty or malformed is not documented; the current logic may match many files.
- `unstagePaths` propagates any `git` error; tests should cover failure scenarios.
- Documentation or type definitions should be updated to expose the new helpers.
- Run the full lint, test, and build suite to confirm no regressions in the new code paths.