

electron/github-commit-context.cjs

Kind: added · Baseline: f7c2bfd81af2 · Target: NovaDiff · Generated: 2026-05-21T10:45:20.222Z

Overview

Adds `electron/github-commit-context.cjs` exposing `getGithubCommitContext(fullName, sha)` to gather pull requests, issues, and comment threads for a commit using the GitHub CLI.

Key changes

- Added `parseJsonSafe(raw, fallback)` (lines 5-12) to safely parse JSON, returning `fallback` on error.
- Added `shortGhError(message)` (lines 13-22) to normalize CLI error messages.
- Added `normalizeThread(entry)` (lines 25-33) to standardize thread objects with defaults.
- Implemented `getGithubCommitContext(fullName, sha)` (lines 40-242) that:
 - Validates `fullName` and `sha`.
 - Checks auth via `getAuthStatus()` (line 52).
 - Executes `gh` commands through `tryRunGh` (line 3) to fetch pulls, issues, PR views, review comments, and issue comments.
 - Aggregates results into `pullRequests`, `issues`, `threads`, and an `error` string.
- Exported via `module.exports = { getGithubCommitContext }` (line 245).

Impact

- Requires the GitHub CLI; errors from `gh` are captured and formatted by `shortGhError`.
- Up to six `gh` calls per commit (pulls, issues, PR view, review comments, issue comments, fallback search).
- Normalized thread objects simplify downstream rendering.
- Errors are concatenated into a single string, allowing callers to display multiple failures.

Risks & follow-ups

- **CLI availability:** If `gh` is not installed or not in PATH, calls will fail.
- **Auth state:** `getAuthStatus` must correctly report login status; otherwise the function returns empty arrays with an error message.
- **Rate limits:** Multiple paginated requests may hit GitHub API limits; monitor for throttling.
- **Parsing edge cases:** `parseJsonSafe` defaults to `fallback` on malformed JSON; callers should handle empty arrays.