

packages/graph-view/src/GraphEmbedSyncBridge.tsx

Kind: added · Baseline: f7c2bfd81af2 · Target: NovaDiff · Generated: 2026-05-21T11:11:26.867Z

Overview

A new React component `GraphEmbedSyncBridge` is added to `packages/graph-view/src/GraphEmbedSyncBridge.tsx` (lines 1-71). It synchronizes embed-graph selection and navigation state with the NovaDiff documentation workspace.

Key changes

- **Imports** (R1-R8):

```
``ts import { useEffect, useRef } from "react"; import { useDashboardStore } from "./store"; import { applyGraphCityRoot, applyGraphEnterFile, applyGraphFocusSelection, type GraphCityNavStore, } from "./utils/graphCityNavigation";
```

– ****Exported API**** (R11-R20):

```
ts export function GraphEmbedSyncBridge({ controlledNodeId, enteredFilePath, focusMode, onSelectionChange, }: { controlledNodeId?: string | null; enteredFilePath?: string | null; focusMode?: boolean; onSelectionChange?: (nodeId: string | null) => void; }) { ... }
```

****State access**** (R22-R24): reads `selectedNodeId` and `graph` from `useDashboardStore`.

- **Store API helper** (R27-R36): `storeApi()` returns navigation functions from the global store state.
- **Navigation effect** (R39-R57): watches `enteredFilePath`, `controlledNodeId`, `focusMode`, and `graph`. Builds a `navKey` and calls the appropriate helper (`applyGraphEnterFile`, `applyGraphFocusSelection`, or `applyGraphCityRoot`).
- **Selection emission** (R59-R67): emits `selectedNodeId` changes via `onSelectionChange`, guarded by a `lastEmitted` ref.
- **Return value** (R70-R71): renders `null`.

Impact

- The component introduces a side-effect path that depends on the presence of `useDashboardStore` in the component's context.
- Navigation helpers are invoked with `controlledNodeId ?? null`; callers must ensure these helpers handle `null` values.
- The `navKey` logic prevents redundant navigation when props remain unchanged.

Risks & follow-ups

- Verify that `useDashboardStore` is available; otherwise the hook will throw.
- Confirm that `applyGraphEnterFile`, `applyGraphFocusSelection`, and `applyGraphCityRoot` correctly handle `null` / `undefined` arguments.
- Test the `navKey` logic with rapid prop changes to ensure no unnecessary navigation occurs.

- Add unit tests for the two `useEffect` branches to guard against regressions in dependency arrays or ref updates.