

packages/graph-view/src/utils/graphCityNavigation.ts

Kind: added · Baseline: f7c2bfd81af2 · Target: NovaDiff · Generated: 2026-05-21T11:14:50.578Z

Overview

A new utility module `packages/graph-view/src/utils/graphCityNavigation.ts` (lines R1-R71) adds navigation helpers for the city view of the knowledge graph.

Key changes

- **Imports** – added at R1-R2 ``ts import type { KnowledgeGraph } from "@novadiff/graph-core/types"; import { resolveGraphNodeFilePath } from "../selectionCluster";

`` - **containerIdForFilePath** – exported at R5; returns `"container:~"` for paths without a slash or `"container:<top>"` for the first folder segment.

- **GraphCityNavStore interface** – defined at R14-R22; requires callbacks for depth entry, node navigation, selection, focus, container expansion, and collapsing all containers.
- **applyGraphCityRoot** – exported at R23; resets the store to the city root by calling `enterNovaDiffEmbedDepth`, `collapseAllContainers`, `selectNode(null)`, and `setFocusNode(null)`.
- **expandFileContainer** – internal helper at R30-R38; expands the container derived from a file path via `containerIdForFilePath`.
- **applyGraphEnterFile** – exported at R40; enters a file node, expands its container, navigates to the target node (`nodeId` or `"file:<path>"`), and sets focus if a node ID is supplied.
- **applyGraphFocusSelection** – exported at R56; synchronizes a graph selection with the city view. It resolves the file path of `nodeId`, expands the relevant container(s), navigates to the node, and sets focus.

Impact

- Centralizes navigation side-effects in a single module, reducing duplication.
- No existing APIs are altered; consumers must implement `GraphCityNavStore` to use these helpers.
- Behavior is deterministic; no new logs or metrics are introduced.

Risks & follow-ups

- **Store implementation** – any missing method in `GraphCityNavStore` will cause runtime errors.
- **resolveGraphNodeFilePath** – called with `graph: KnowledgeGraph | null`; ensure it handles `null` safely.
- **Edge cases** – test `containerIdForFilePath` with paths lacking slashes or empty strings to confirm correct container IDs.

- **Container expansion** – `expandFileContainer` only expands; verify it does not unintentionally collapse unrelated containers.