

electron/gh-install.cjs

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:21:09.086Z

Overview

A new module `electron/gh-install.cjs` (lines 1-196) is added to the Electron build. It implements runtime detection, installation, and status reporting for the GitHub CLI (`gh`) on macOS, Windows, and Linux.

Key changes

- **Imports** – `spawn` / `spawnSync` from `node:child_process` and `fssync` from `node:fs` are added (R3, R4, R24, R85).
- `resolveBrew()` (lines 15-38) checks known Homebrew paths or runs `command -v brew`.
- `getInstallPlan()` (lines 40-79) returns an object with `canAutoInstall`, `method`, `command`, and URLs, tailored per platform.
- `readGhVersion()` (lines 81-94) runs `gh --version` via `spawnSync` to capture the installed version.
- `getGhToolingStatus()` (lines 96-110) aggregates installation status, path, version, and plan details.
- `runInstallCommand()` (lines 116-142) spawns the install command, streams output to an optional logger, and clears the `gh` cache on completion.
- `installGh()` (lines 148-190) orchestrates the installation flow, validates success, and returns the installed path and version.
- **Exports** (lines 192-196) expose `GH_FEATURE_REASON`, `getGhToolingStatus`, and `installGh`.

Impact

- **Deterministic checks** – `spawnSync` is used for quick existence and version queries, reducing nondeterminism.
- **Centralized logic** – All CLI tooling concerns live in one module; adding a new platform only requires extending `getInstallPlan()`.
- **Responsive UI** – `runInstallCommand()` is async, keeping the Electron UI responsive during installs.
- **Explicit URLs** – Manual install hints point to `https://cli.github.com/` and platform-specific resources.
- **Logging** – Optional `onLog` streams install output, aiding debugging.

Risks & follow-ups

- **Homebrew detection** – `resolveBrew()` relies on known paths and `command -v brew`; verify it finds Homebrew on all supported macOS variants.
- **Cache invalidation** – `clearGhCache()` is called before and after installs; missing it could leave stale state.

- **Permission handling** – Homebrew or winget installs may require elevated privileges; test error paths.
- **Linux support** – No auto-install is offered; confirm `isGhInstalled()` correctly reports absence.