

electron/gh-path.cjs

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:21:50.765Z

Overview

A new module `electron/gh-path.cjs` is added. It supplies helpers to locate the GitHub CLI binary, augment the PATH for GUI-app contexts, and generate platform-specific install hints.

Key changes

- `augmentPathForCli` (lines 38-51): builds a new environment object that merges Homebrew/user bin directories; it does not modify `process.env`.
- `extraPathDirs` (lines 15-31): lists common binary locations, including Windows `LOCALAPPDATA`.
- `ghCandidatePaths` (lines 53-60): enumerates typical `gh` install locations.
- `resolveViaLoginShell` (lines 63-90): runs `/bin/zsh` or `/bin/bash` with `-ilc` / `-lc` to execute `command -v gh`; returns the path if found.
- `resolveGhExecutable` (lines 104-138): performs a multi-step lookup—cache, candidate paths, login shell, `which/where`, then defaults to `"gh"` or `"gh.exe"`. Uses `cachedGhPath` to avoid repeated `spawnSync`.
- `verifyGh` (lines 92-99): runs `gh --version` to confirm the binary works.
- `ghInstallHint` (lines 152-160) and `**ghNotFoundError*`
- (lines 162-164): provide platform-specific guidance.
- The module exports all helpers (lines 166-173).

Impact

- Centralizes path logic for macOS, Windows, and Linux; functions are small, exported, and testable.
- Caching reduces repeated synchronous child-process calls.
- Explicit handling of Windows (`where` , `gh.exe`) and macOS Homebrew paths.
- Errors include install hints, improving user experience.

Risks & follow-ups

- `spawnSync` calls block startup; verify latency on all target platforms.
- `resolveViaLoginShell` assumes `/bin/zsh` or `/bin/bash` exist; test on minimal images or custom macOS setups.
- If `gh` is installed/uninstalled after app start, `clearGhCache` must be called; ensure callers invoke it.
- `augmentPathForCli` merges directories but does not alter global `process.env`; downstream modules must use the returned environment.