

electron/github-service.cjs

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:25:24.629Z

Overview

A new module `electron/github-service.cjs` is added. It wraps the GitHub CLI (`gh`) and exposes functions for authentication status, repository and pull-request listing, PR creation, and account detection.

Key changes

- **Imports added** (diff lines R3-R9):
`spawnSync` from `node:child_process`, `parseGithubSlugFromUrl` from `./git-service.cjs`, and `augmentPathForCli`, `resolveGhExecutable`, `ghNotFoundError` from `./gh-path.cjs`.
- **CLI helpers** (lines 11-29): `runGh` executes a command via `spawnSync`; `tryRunGh` wraps it in a try/catch.
- **Auth & user** (lines 43-76, 163-177): `getAuthStatus`, `getUserProfile`.
- **Repository & PR utilities** (lines 77-128, 129-161): `listRepos`, `listPullRequests`, `viewPullRequest`, `createPullRequest`.
- **Account detection** (lines 179-200): `listDetectedAccounts`.
- **Slug extraction** (lines 203-210): `slugFromRepoRoot`.
- **Exports** (lines 213-224): all functions are exported via `module.exports`.

Impact

- Provides runtime checks for CLI availability and authentication state, reducing silent failures.
- Centralizes all `gh` interactions, simplifying future flag or command changes.
- Each call spawns a new process (`spawnSync`), which may add overhead for bulk operations but is acceptable for UI-driven actions.
- Requires the `gh` executable; when missing, functions return informative messages (e.g., `getAuthStatus`).

Risks & follow-ups

- **Missing tests:** No unit tests cover the new module; add tests for `getAuthStatus` and `listRepos`.
- **Error handling:** `runGh` throws generic errors; ensure callers handle them gracefully.
- **Platform differences:** `spawnSync` and CLI path resolution may behave differently on Windows; verify across all target OSes.
- **Security:** `createPullRequest` builds CLI arguments from user input; review for potential injection vulnerabilities.