

electron/preload.cjs

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:31:04.198Z

Overview

A new file `electron/preload.cjs` (lines 1-183) is added. It imports `contextBridge` and `ipcRenderer` from Electron and exposes a global `electronAPI` object to the renderer via `contextBridge.exposeInMainWorld`.

Key changes

- **API surface** – `electronAPI` now contains many `ipcRenderer.invoke` wrappers (e.g., `compareFolders`, `getFileDiff`, `pickDirectory`, `gitRepoStatus`, `workspaceCreate`, `llmSummarize`, etc.) as shown in the added lines 9-52, 58-71, 73-80, 82-84, 88-116, 117-120, 122-128, 130-140, 142-149, 151-158, 160-172, 174-181.
- **Event listeners** – Added helpers such as `onWindowStateChange`, `onKnowledgeGraphProgress`, `onEngineProgress`, `onSummaryPrefetchProgress`, `onGithubGhInstallProgress`, `onGithubAuthProgress`, `onWorkspaceHistoryProgress` (lines 19-27, 55-62, 64-71, 73-80, 151-158, 165-172, 174-181) that register IPC listeners and return cleanup callbacks.
- **Constants** – Introduced `LLM_STREAM` and `WINDOW_STATE` tokens (lines 5-6).
- **LLM streaming** – Implemented `llmSummarizeStream` (lines 88-116) that aborts any previous stream, listens on `LLM_STREAM`, and streams accumulated text via a callback.
- **Context isolation** – Uses `require("electron")` and `contextBridge` to safely expose APIs.

Impact

- **Renderer access** – Front-end code can call backend features directly; corresponding main-process handlers must exist.
- **Preload linkage** – The script must be referenced in `webPreferences.preload` for all renderer windows; tests should verify this configuration.
- **Security** – Exposing many APIs requires strict context isolation and input validation to prevent misuse.

Risks & follow-ups

- **Missing handlers** – If any invoked channel lacks a main-process handler, renderer calls will fail; run integration tests to confirm all handlers exist.
- **Listener leaks** – Ensure cleanup callbacks returned by the `on...` helpers are invoked; otherwise listeners may accumulate.
- **Performance** – Unknown from the available diff/scan evidence; monitor IPC traffic for large file diffs or LLM streams.

- **Compatibility** – Existing renderer code that does not expect `electronAPI` should handle its absence gracefully; add defensive checks if needed.