

electron/repo-discovery.cjs

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:31:41.653Z

Overview

`electron/repo-discovery.cjs` is a new module that discovers local Git repositories, extracts remote slugs, and exposes a discovery API for the Electron front-end.

Key changes

- **Imports** (lines 1-6): ``js const fssync = require("node:fs"); const path = require("node:path"); const os = require("node:os"); const { parseGithubSlugFromUrl, tryRunGit } = require("./git-service.cjs");

```
`SKIP_DIR_NAMES` set, `MAX_REPOS = 120`, `MAX_DEPTH = 4`.
- **`homeSearchRoots()`** (lines 29-68): builds a platform-aware list of candidate home
directories, deduplicates, and validates existence.
- **`readGitRemoteSlug(repoRoot)`** (lines 70-86): runs `git remote -v`, parses the first fetch
URL, and returns `{owner, repo, remote, url}` or `null`.
- **`scanForGitRepos(root, opts)`** (lines 88-141): recursively walks each root up to `MAX_DEPTH`,
skips `SKIP_DIR_NAMES` and dot-folders, collects up to `MAX_REPOS` repos, optionally filtering by
`targetSlug`.
- **`discoverRepos(payload)`** (lines 143-155): merges home roots with any `extraRoots`, invokes
`scanForGitRepos`, and returns `{searchRoots, matches, scannedAt}`.
- **`matchRepoForGithubRepo(owner, repo, extraRoots)`** (lines 157-158): convenience wrapper that
returns only the matched repos.
- **Exports** (lines 161-166): exposes `homeSearchRoots`, `discoverRepos`,
`matchRepoForGithubRepo`, and `readGitRemoteSlug`.
```

Impact

- Centralizes discovery logic; future changes can be made in one place.
- Scans up to 120 repos with a depth limit of 4, returning a `scannedAt` timestamp for observability.
- Uses Node 18

+ `node:` imports, which may not be available in older Electron builds.

Risks & follow-ups

- **Scan performance**: scanning large directories may block the UI; consider async or worker-thread implementation if needed.
- **Missing `git`**: `tryRunGit` should handle environments without Git; add unit tests for this scenario.
- **Duplicate roots**: `homeSearchRoots` deduplicates via a `seen` set, but `extraRoots` may still introduce duplicates; confirm no double-counting in `discoverRepos`.

- **Cross-platform path handling**: test on Windows, macOS, and Linux to ensure `path.join` and `path.resolve` produce correct results, especially for Windows drive letters.