

electron/workspace-files.cjs

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:32:24.468Z

Overview

A new CommonJS module `electron/workspace-files.cjs` (R1-85) adds snapshot-file utilities for the Electron renderer. It exports two async functions: `listSnapshotFiles` and `readSnapshotTextFile`.

Key changes

- **Imports** (R3-R5): `node:fs`, `node:fs/promises`, and `node:path` are required for file system access and path resolution.
- **SKIP_DIRS** (R7-R14): Directories such as `.git`, `node_modules`, `dist`, `build`, `target`, `.novadiff-graph`, and `snapshots` are excluded from traversal.
- **listSnapshotFiles** (R17-R58):
 - Resolves the root with `path.resolve` (R18).
 - Limits to `maxFiles` (default 2500) (R19).
 - Recursively walks the tree, skipping hidden files except `.env` (R39-R42) and directories in `SKIP_DIRS` (R47-R49).
 - Returns a sorted array of relative paths with forward slashes (R58).
- **readSnapshotTextFile** (R61-R80):
 - Validates `snapshotRoot` and `relPath`, rejecting paths containing `..` (R64-R70).
 - Reads the file via `fsp.readFile` (R71).
 - Truncates content to `maxBytes` (default 512 KB) and reports `truncated` and `size` (R72-R79).
- **Exports** (R82-R85): Both functions are exported.

Impact

- **Correctness:** Path validation prevents directory traversal.
- **Safety:** Truncation to `maxBytes` limits memory usage.
- **Convenience:** Centralized snapshot utilities reduce duplication across the repo.

Risks & follow-ups

- **Large directories:** Verify that the `maxFiles` cap and async walk do not block the event loop.
- **Hidden file handling:** Ensure `.env` files remain accessible while other dotfiles are skipped.
- **Path traversal:** Test edge cases where `relPath` contains encoded `..` sequences.
- **Truncation logic:** Confirm that `maxBytes` truncation correctly reports `size` and `truncated` flags.