

packages/graph-core/src/__tests__/layer-detector.test.ts

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T05:57:20.265Z

Overview

A new test file `packages/graph-core/src/__tests__/layer-detector.test.ts` (added lines R1-188) validates the layer-detection logic in the graph core module.

Key changes

- Added imports from `vitest` and the layer-detector API (`detectLayers` , `buildLayerDetectionPrompt` , `parseLayerDetectionResponse` , `applyLLMLayers`) plus type imports from `../types.js` (lines R1-R8).
- Introduced helper constructors `makeNode` and `makeGraph` to build minimal `KnowledgeGraph` objects for tests.
- Test cases cover:
 - `detectLayers` identifies **API**, **Data**, and **Core** layers based on file paths (e.g., `src/routes/` , `src/models/`).
 - Layer IDs start with `layer:` and are unique (lines 86-92).
 - Only nodes of type `file` are included; function and class nodes are ignored (lines 95-106).
 - `buildLayerDetectionPrompt` includes file paths and references JSON (lines 110-118).
 - `parseLayerDetectionResponse` handles plain JSON, markdown-wrapped JSON, and returns `null` for invalid input (lines 122-160).
 - `applyLLMLayers` assigns nodes to LLM-provided layers and places unmatched nodes in an **Other** layer (lines 163-187).

Impact

- Adds ~188 lines of test code, providing concrete coverage for typical project structures.
- Centralizes test helpers for reuse in future tests.
- No snapshots are used; all assertions are direct.

Risks & follow-ups

- If layer-detection logic or regex patterns change, tests may fail; review failures and adjust expectations.
- The ID uniqueness test depends on the `layer:` prefix; any change to ID generation must be reflected.
- Tests are lightweight but should be monitored if graph size grows; consider parameterizing with larger graphs if needed.