

packages/graph-core/src/persistence/index.ts

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T05:30:25.799Z

Overview

A new persistence module (`packages/graph-core/src/persistence/index.ts`) centralises file handling for knowledge graphs, meta, fingerprints, and config. It replaces ad-hoc logic with a single, well-structured API.

Key changes

- **Imports & constants:** added `node:fs` / `node:path` helpers and file names (`GRAPH_FILE` , `META_FILE` , etc.) (lines 1-11).
- `ensureDir(projectRoot)` (lines 13-19) guarantees the `.novadiff-graph` folder exists.
- `sanitiseFilePaths(graph, projectRoot)` (lines 38-66) converts absolute paths to project-relative or just the filename, preventing leakage of developer directories.
- `saveGraph` / `loadGraph` (lines 69-106) now sanitise before persisting and validate on load via `validateGraph` .
- `saveMeta` / `loadMeta` , `saveFingerprints` / `loadFingerprints` , `saveConfig` / `loadConfig` (lines 107-148) provide CRUD for auxiliary data, with graceful fallbacks on missing or malformed files.
- **Domain graph support** (`saveDomainGraph` / `loadDomainGraph` , lines 152-182) mirrors the main graph logic.
- Default config (`DEFAULT_CONFIG`) and error-safe parsing for config files (lines 140-147).

Impact

- Sanitisation removes sensitive absolute paths; validation throws an `Error` on malformed graphs.
- All persistence logic lives in one module, reducing duplication.
- Default config is returned when the file is absent or corrupted.

Risks & follow-ups

- Verify `sanitiseFilePaths` correctly handles paths inside, outside, and already relative to `projectRoot` .
- Callers of `loadGraph` / `loadDomainGraph` must handle thrown errors or disable validation (`options?.validate === false`).
- Confirm `loadConfig` returns the intended defaults when the file is missing or corrupted.
- Ensure the new module is re-exported from the package's public index so external consumers can access these helpers.