

packages/graph-view/src/App.tsx

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T05:16:26.373Z

Overview

`packages/graph-view/src/App.tsx` replaces the previous bootstrap. The file now imports React hooks (`useEffect` , `useState` , `useMemo` , `useCallback` , `lazy` , `Suspense`) and validation utilities (`validateGraph` , `GraphIssue`) – see lines 1–6.

A demo flag (`DEMO_MODE`) and session-storage token logic are added in `dataUrl` (lines 41–55) and `resolveInitialToken` (lines 61–75). `App` (lines 78–97) renders a `TokenGate` when no token is present, otherwise passes the token to `Dashboard` .

`Dashboard` (lines 99–210) fetches meta, config, knowledge, diff-overlay, and domain graphs, validates them, and updates the global store via `useDashboardStore` . `DashboardContent` (lines 211–735) orchestrates the UI: header, sidebar, graph view, code viewer, inspector, and modals, with mobile-aware layout and keyboard shortcuts.

Heavy components (`CodeViewer` , `LearnPanel` , `PathFinderModal` , `KeyboardShortcutsHelp`) are lazy-loaded (lines 28–34). The file ends with `export default App;` (line 735).

Key changes

- **Imports:** added React hooks and validation utilities (lines 1–6).
- **Token logic:** `dataUrl` and `resolveInitialToken` build URLs based on `DEMO_MODE` and session storage (lines 41–75).
- **App:** renders `TokenGate` or `Dashboard` depending on token presence (lines 78–97).
- **Dashboard:** fetches and validates data, updates store (lines 99–210).
- **DashboardContent:** full UI composition, keyboard shortcuts, mobile layout (lines 211–735).
- **Lazy loading:** heavy modules imported with `lazy` (lines 28–34).
- **Export:** `export default App;` (line 735).

Impact

- **Token handling:** centralizes token acquisition and persistence.
- **Validation:** errors surface via `WarningBanner` (lines 626–628).
- **Performance:** lazy loading reduces initial bundle size.
- **Demo mode:** bypasses token gate when `VITE_DEMO_MODE=true` .
- **UI:** single file contains all layout logic, easing navigation.

Risks & follow-ups

- **Token persistence:** verify `resolveInitialToken` clears the URL and stores the token (lines 61–75).
- **Lazy-load failures:** ensure missing chunks (e.g., `CodeViewer`) are handled gracefully.

- **Demo mode flag:** confirm `VITE_DEMO_MODE` is set correctly; otherwise the token gate may be skipped.
- **Store updates:** check that `setGraph` , `setDomainGraph` , etc., are called only after successful validation (lines 123-149, 180-196).