

packages/graph-view/src/components/CodeViewer.tsx

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T06:03:29.338Z

Overview

A new `CodeViewer` component is added at `packages/graph-view/src/components/CodeViewer.tsx` (lines 1-415). It renders a syntax-highlighted source file, allows line-range selection, and can open an "Explain code" modal via the NovaDiff embed context.

Key changes

- **Imports** (R1-6): React hooks, `createPortal`, Prism-renderer (`Highlight`, `themes`), and local contexts (`useDashboardStore`, `useI18n`, `useNovaDiffEmbed`).
- **Interfaces** (R9-15, R16-22): `CodeViewerProps` (`accessToken`, `presentation`, `callbacks`) and `SourceFile` (`path`, `language`, `content`, `sizeBytes`, `lineCount`).
- **Utility functions** (R29-33, R34-55, R56-60): `fileContentUrl`, `fallbackLanguage`, and `formatBytes`.
- **Component export** (R62): `export default function CodeViewer(...)`.
- **Logic:**
 - Retrieves graph data via `useDashboardStore`.
 - Loads file content with `fetch` or `embed.readFile`; demo mode (`__demo__`) blocks loading.
 - Manages selection state (`selectAnchor`, `selectEnd`) and runs `runExplainCode` to stream explanation text to a portal modal.
 - Renders a Prism `Highlight` block with line numbers, node-highlighting, and user selection highlighting.

Impact

- **Correctness:** Asynchronous loading and error handling are present; errors are displayed in a styled card.
- **Maintainability:** All logic resides in a single file; helper functions and interfaces keep the component readable.
- **Performance:** Rendering large files may be heavy due to Prism tokenization; selection updates are memoized.
- **Compatibility:** The component is isolated but requires the `useNovaDiffEmbed` and `useDashboardStore` contexts to be provided.

Risks & follow-ups

- **No tests:** The diff shows no new tests; coverage for loading, error states, and explain flow is unknown.
- **Large file rendering:** Potential performance impact from Prism tokenization is unknown from the diff.

- **Context availability:** The component assumes `useNovaDiffEmbed` and `useDashboardStore` are present; verify that these contexts are provided in all relevant routes.
- **Demo mode guard:** The `__demo__` token check may block legitimate use cases; confirm demo environment configuration.