

packages/graph-view/src/contexts/I18nContext.tsx

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T05:31:33.446Z

Overview

A new i18n context module was added at `packages/graph-view/src/contexts/I18nContext.tsx`. It introduces a `useI18n` hook and an `I18nProvider` component for locale handling.

Key changes

- **Imports** (lines 1-2): `createContext`, `useContext`, `useMemo`, `ReactNode` from `react`; `getLocale`, `resolveLocaleKey`, `Locale`, `LocaleKey` from `../locales`.
- **Interface** (lines 4-7): `I18nContextValue` exposes `locale: Locale`, `localeKey: LocaleKey`, and `t: Locale`.
- **Context** (line 10): `I18nContext` initialized with `null`.
- **Hook** (lines 12-18): `useI18n()` retrieves the context and throws if called outside a provider.
- **Provider** (lines 20-44): accepts optional `language` and `children`, memoizes `localeKey` and `locale`, and supplies `{ locale, localeKey, t: locale }` to the context.

Impact

- Components must be wrapped in `I18nProvider`; otherwise `useI18n` throws an error.
- Locale logic is centralized, simplifying future changes to language resolution.
- `useMemo` keeps `localeKey`, `locale`, and the context value stable across renders, reducing unnecessary re-renders.

Risks & follow-ups

- `t` is currently the locale object; if a translation function is intended, the implementation should be updated.
- Verify that `getLocale` and `resolveLocaleKey` return correct values for all supported languages.
- Run lint, tests, and a production build to confirm no type or runtime errors.
- Add unit tests for `useI18n` throwing behavior and provider value correctness.