

packages/graph-view/src/contexts/NovaDiffEmbedContext.tsx

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T05:32:21.496Z

Overview

A new file `packages/graph-view/src/contexts/NovaDiffEmbedContext.tsx` has been added. It introduces a React context that exposes NovaDiff embed functionality to the graph-view package.

Key changes

- **Imports** – `createContext` and `useContext` from React are imported (line 1).
- **NovaDiffSourceFile** (lines 3-9) declares file metadata: `path`, `language`, `content`, `sizeBytes`, `lineCount`.
- **ExplainCodeRequest** (lines 11-17) defines the payload for LLM-based code explanations.
- **NovaDiffEmbedContextValue** (lines 19-27) lists optional members: `readFile`, `embedMode`, and `explainCode`.
- **Context creation** – `NovaDiffEmbedContext` is created with a default empty object (line 30).
- **Hook** – `useNovaDiffEmbed` (lines 32-34) returns `useContext(NovaDiffEmbedContext)`.

No other files were modified; the change is purely additive.

Impact

The new context provides a public API for embedding NovaDiff features. Because the default value is `{}`, any consumer that does not wrap its component tree with `NovaDiffEmbedContext.Provider` will receive `undefined` for the optional members. This can lead to runtime errors if callers attempt to invoke `readFile` or `explainCode` without checking for existence.

Risks & follow-ups

- **Provider requirement** – The diff does not show any existing consumers; verify that components using `useNovaDiffEmbed` are wrapped in a provider to avoid `undefined` values.
- **Runtime safety** – Guard against `undefined` callbacks; consider adding defensive checks or default no-op implementations.
- **Type coverage** – The empty default satisfies the TypeScript type but may mask missing properties during development; run linting to confirm no required fields are omitted.
- **Testing** – Add unit tests that supply a provider and assert that `readFile` and `explainCode` are called correctly.