

packages/graph-view/src/hooks/useIsMobile.ts

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T05:33:32.447Z

Overview

A new hook, `useIsMobile`, is added at `packages/graph-view/src/hooks/useIsMobile.ts`. It returns a boolean indicating whether the viewport width is below a configurable breakpoint (default 768px).

Key changes

- Import `useEffect` and `useState` from `react` (R1).
- Define `DEFAULT_BREAKPOINT = 768` (R3).
- Export `useIsMobile(breakpoint = DEFAULT_BREAKPOINT)` (R5).
- Build media query `(max-width: ${breakpoint - 1}px)` (R6).
- Initialize state with `useState<boolean>`; guard against SSR (`typeof window === "undefined"` returns false) (R7-R9).
- `useEffect` creates a `MediaQueryList`, updates state on change, and removes the listener on cleanup (R12-R18).
- Return the current `isMobile` state (R20-R21).

Impact

- SSR-safe: returns `false` when `window` is undefined.
- Single source of truth for breakpoint logic; default can be adjusted.
- Minimal overhead: one event listener per hook instance.
- Works in browsers supporting `matchMedia` and `addEventListener` on `MediaQueryList`.

Risks & follow-ups

- Verify `matchMedia` support in target browsers; fallback may be needed for legacy environments (unknown from the available diff/scan evidence).
- Confirm cleanup correctly removes the listener to avoid memory leaks.
- Test the hook in SSR contexts (e.g., Next.js) to ensure no crashes.
- Ensure that changing the `breakpoint` prop updates the listener and state as expected.