

packages/graph-view/src/hooks/useKeyboardShortcuts.ts

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T05:34:04.975Z

Overview

`packages/graph-view/src/hooks/useKeyboardShortcuts.ts` adds a reusable hook for global keyboard shortcuts and a helper to format shortcut keys for display.

Key changes

- **Import:** `useEffect` from React (line 1).
- **Interface:** `KeyboardShortcut` (lines 3-12) defines `key`, optional modifier flags (`ctrlKey`, `shiftKey`, `altKey`, `metaKey`), `description`, `action`, and `category`.
- **Hook:** `useKeyboardShortcuts(shortcuts, enabled = true)` (lines 14-51) registers a `keydown` listener via `useEffect`.
 - Skips shortcuts when the event target is an `<input>`, `<textarea>`, or content-editable element, unless the key is `Escape`.
 - Matches the pressed key and modifiers against each shortcut, using `!event.modifier` when the shortcut flag is undefined.
 - Calls `event.preventDefault()` when `ctrlKey`, `metaKey`, or `altKey` are active to avoid browser conflicts, then executes the shortcut's `action`.
- **Formatter:** `formatShortcutKey(shortcut)` (lines 52-71) builds a human-readable string.
 - Detects macOS via `navigator.userAgentData?.platform` or `navigator.platform`.
 - Adds symbols `⌘`, `⇧`, `⌘` for `metaKey`, `shiftKey`, and `altKey` respectively, omitting `⇧` for punctuation that requires shift.
 - Appends the key in uppercase or the original character if it is shifted punctuation.

Impact

- Centralizes shortcut logic, simplifying addition or modification of shortcuts across the app.
- Provides a single global `keydown` listener per component mount, with an early return when `enabled` is `false`.
- Offers platform-aware key labels for tooltips or help dialogs.

Risks & follow-ups

- **Browser shortcut conflicts:** Verify that common shortcuts (e.g., `Ctrl+S`, `⌘+Z`) still function after `preventDefault()` is applied.
- **Meta key detection:** The matching logic defaults to `!event.metaKey` when `shortcut.metaKey` is omitted; tests should cover this case.
- **Shift-punctuation handling:** `formatShortcutKey` omits `⇧` for punctuation; confirm this matches user expectations.

- **Testing coverage:** Add unit tests for `useKeyboardShortcuts` covering input bypass, modifier matching, and default prevention.