

packages/graph-view/src/store.ts

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T05:22:11.148Z

Overview

A brand-new `packages/graph-view/src/store.ts` file introduces a Zustand-based state store for the graph view, along with a suite of helper types and functions for graph indexing, tour navigation, and layout caching.

Key changes

- **New imports:** `zustand`, `SearchEngine`, `SearchResult`, `GraphIssue`, `ReactFlowInstance`, and `PROJECT_WIDE_LAYER_ID` from `./utils/activeLayer`.
- **Public types:** `Persona`, `NavigationLevel`, `NodeType`, `Complexity`, `EdgeCategory`, `ViewMode`, `DetailLevel`, and `FilterState` (lines 21-74).
- **Graph indexing:** `buildGraphIndexes` (lines 75-95) creates `nodesById`, `nodeIdToLayerId`, and `nodeIdToLayerIds` maps.
- **Tour helpers:** `getSortedTour` (lines 249-251), `navigateTourToLayer` (lines 255-267), and `layerResetIfChanged` (lines 279-293) manage tour state and reset layout caches when the active layer changes.
- **Store definition:** `DashboardStore` interface (lines 101-247) and `useDashboardStore` (lines 296-858) expose state slices and actions for graph loading, navigation, filtering, diff overlay, tour control, view mode, and container layout caching.
- **Layout issue handling:** `appendLayoutIssues` and `clearLayoutIssues` (lines 845-857) aggregate ELK repair warnings.

Impact

- **Correctness:** The new store centralises graph-related state, reducing duplicated logic in components.
- **Maintainability:** All state mutations are now typed and encapsulated; future extensions can add actions without touching component logic.
- **Performance:** Large `Map` structures are rebuilt on `setGraph`; careful to avoid unnecessary re-renders by resetting caches only when needed (e.g., `layerResetIfChanged`).
- **Compatibility:** Existing components must import `useDashboardStore` instead of previous ad-hoc state; missing imports will surface at compile time.
- **Observability:** `layoutIssues` and `appendLayoutIssues` provide a single source for ELK warnings, simplifying debugging.

Risks & follow-ups

- **Tour navigation regressions:** Verify that `navigateTourToLayer` correctly sets `navigationLevel` and `activeLayerId` for all tour steps.

- **Cache invalidation:** Ensure `layerResetIfChanged` clears caches only when the layer actually changes; accidental resets could degrade layout performance.
- **Filter defaults:** `DEFAULT_FILTERS` uses `new Set` copies; confirm that mutations in actions (`setFilters`, `resetFilters`) do not leak shared references.
- **Type exposure:** The new public types (`Persona`, `NavigationLevel`, etc.) are exported; confirm no naming clashes with existing modules.