

packages/graph-view/src/themes/ThemeContext.tsx

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T05:37:36.906Z

Overview

`packages/graph-view/src/themes/ThemeContext.tsx` now defines a React context for theme handling.

- New context type `ThemeContextValue` (lines 17-26).
- `ThemeContext` created with `createContext<ThemeContextValue | null>(null)` (line 25).
- `ThemeProvider` component (lines 66-147) and `useTheme` hook (lines 148-152) are exported.

Key changes

- **Imports** (lines 1-13): added `createContext`, `useCallback`, `useContext`, `useEffect`, `useRef`, `useState`, `type ReactNode`; type imports from `./types.ts`; constants and helpers from `./presets.ts` and `./theme-engine.ts`.
- **Persistence helpers:** `loadFromLocalStorage` (lines 27-40) and `saveToLocalStorage` (lines 41-47) read/write the key `"ua-theme"`.
- **Initial theme resolution:** `resolveInitialTheme` (lines 49-58) chooses between `metaTheme`, `localStorage`, or `DEFAULT_THEME_CONFIG`.
- **Provider logic:**
 - State initialized via `resolveInitialTheme`.
 - `useEffect` applies theme on mount/update; saves to `localStorage` only when `scopeToHost` is false and the component has mounted (lines 75-90).
 - Cleanup `clearTheme` on unmount when `scopeToHost` is true (lines 92-102).
 - Async `metaTheme` updates handled in a separate `useEffect` (lines 104-113).
- **Setters:** `setPreset`, `setAccent`, `setHeadingFont` memoized with `useCallback` (lines 115-128).
- **Context value:** `{ config, preset, setPreset, setAccent, setHeadingFont }` (line 133).
- **Hook:** `useTheme` throws if used outside a provider (lines 148-152).

Impact

- **Single source of truth:** Theme state lives only in `ThemeProvider` state and context.
- **Persistence:** User preferences survive page reloads via `localStorage` unless overridden by `metaTheme`.
- **Scoped theming:** `scopeToHost` allows tokens to apply only to a wrapper element, useful for embedded graphs.
- **Error handling:** `LocalStorage` errors are caught silently, preventing crashes but hiding failures.
- **Consumer migration:** Components must now be wrapped in `ThemeProvider` or use `useTheme`.

Risks & follow-ups

- **Silent storage failures:** `saveToLocalStorage` and `loadFromLocalStorage` swallow errors; verify fallback behavior is acceptable.
- **Provider usage:** `useTheme` throws if called outside a provider; ensure all consumers are updated.
- **Scope flag logic:** `clearTheme` runs only on unmount when `scopeToHost` is true; confirm cleanup works in embedded scenarios.
- **Async metaTheme:** The provider updates config when `metaTheme` arrives after mount; test that this does not overwrite a user-selected preset stored in `localStorage`.