

packages/graph-view/src/utils/activeLayer.ts

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T05:45:11.983Z

Overview

A new file `packages/graph-view/src/utils/activeLayer.ts` is added. It exports a helper that resolves an active layer ID into a detailed layer object, including a synthetic "project-wide" layer.

Key changes

- **Import** (line 1, R1): `import type { KnowledgeGraph } from "@novadiff/graph-core/types";`
- **Constant** (line 4, R4): `export const PROJECT_WIDE_LAYER_ID = "__novadiff_project__";`
- **Function** (lines 6-9, R6-9): `export function resolveActiveLayer( graph: KnowledgeGraph, activeLayerId: string | null ): { id: string; name: string; description: string; nodeIds: string[] } | null`

```- **Project-wide logic**` (lines 13-26, R13-26): if `activeLayerId === PROJECT_WIDE_LAYER_ID`, aggregates all node IDs from every layer; if no layers exist, falls back to nodes that have a `layerId`.

- **Normal layer lookup** (lines 34-43, R34-43): finds the matching layer in `graph.layers` and returns its metadata.
- **Null handling** (lines 10-12, 35-36, R10-12, R35-36): returns `null` when `graph` or `activeLayerId` is falsy, or when no matching layer is found.

### Impact

- Provides a single source of truth for layer resolution; callers can import `resolveActiveLayer` from this file.
- No API changes to existing modules; the new function is purely an internal helper. (unknown from the available diff/scan evidence)

### Risks & follow-ups

- Verify that `PROJECT_WIDE_LAYER_ID` does not collide with real layer IDs in existing projects.
- Ensure node aggregation correctly handles cases where `graph.layers` is empty but `graph.nodes` contains nodes without `layerId`.
- Add unit tests for both the synthetic layer path and normal layer resolution.
- Confirm callers correctly import and use `resolveActiveLayer`; update documentation if necessary.