

scripts/run-electron.cjs

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:12:27.032Z

Overview

A new script `scripts/run-electron.cjs` is added. It spawns the Electron binary from `node_modules/electron/dist/` instead of using `electron/cli.js`. The script resolves the binary path, cleans the environment, and starts the process with the supplied arguments.

Key changes

- **Imports** (R9-R11): `fs`, `path`, and `spawn` from Node core modules; `augmentPathForCli` from `path.join(root, "electron", "gh-path.cjs")` (R18).
- `cleanEnv()` (lines 17-22): augments `PATH` via `augmentPathForCli`, removes `ELECTRON_OVERRIDE_DIST_PATH`, returns sanitized env.
- `resolveElectronBinary()` (lines 24-41): reads `path.txt` in the Electron package, validates existence of the binary, returns its full path. Throws if `path.txt` missing or empty, or binary not found.
- **Process launch** (lines 49-53): spawns the binary with `cwd: root`, `stdio: "inherit"`, and the cleaned env.
- **Error handling** (lines 55-66): logs child errors, exits with child's exit code or forwards signals.

Impact

The script guarantees the binary used is the one bundled with the repo, avoiding overridden paths. Centralizes binary resolution logic; future changes to Electron layout can be made in one place. Errors are printed to stdout and the process exits with the child's exit code, aiding debugging.

Risks & follow-ups

- **Missing `path.txt`**: script throws if absent; ensure `npm install` populates it.
- **Node version**: relies on `node:fs`, `node:path`, `node:child_process`; requires Node 18+.
- **`augmentPathForCli` `path`**: script assumes `path.join(root, "electron", "gh-path.cjs")` exists and exports correctly; validate this dependency.
- **Testing**: add unit tests for `resolveElectronBinary()` and `cleanEnv()` to cover edge cases such as empty `path.txt` or missing binary.