

src/app/generatedMarkdown.ts

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:42:53.219Z

Overview

A new module `src/app/generatedMarkdown.ts` was added. It exports a single function, `normalizeGeneratedMarkdown`, that cleans up markdown before rendering.

Key changes

- `normalizeGeneratedMarkdown` (lines 141-150)
- Sanitizes malformed fences (`normalizeMalformedCodeFences`).
- Splits the source on fenced code blocks and applies either `normalizeFenceChunk` or `normalizeMarkdownChunk`.
- `normalizeFenceChunk` (lines 52-68)
- Trims fence bodies.
- Detects raw diff dumps via `looksLikeRawDiffDump` (lines 38-51) and replaces them with the placeholder `_Raw diff excerpt omitted from saved summary._`.
- `normalizeMarkdownChunk` (lines 126-138)
- Promotes known headings (`promoteKnownHeadings`, lines 78-104).
- Normalizes compact list markers (`normalizeCompactListMarkers`, lines 69-76).
- Splits dense paragraphs when the block exceeds 560 characters.
- `promoteKnownHeadings` (lines 78-104) ensures that headings from the `KNOWN_SECTION_HEADINGS` array are consistently formatted and spaced.
- `normalizeCompactListMarkers` (lines 69-76) rewrites list markers to avoid accidental heading promotion.
- `looksLikeRawDiffDump` (lines 38-51) heuristically detects diff-style text to avoid leaking raw diffs in summaries.

Impact

- Centralizes markdown cleanup logic; no existing exports are altered.
- Adds a placeholder for raw diff excerpts, reducing accidental leakage of diff content.

Risks & follow-ups

- **Regex over-matching:** Verify that `normalizeCompactListMarkers` and `promoteKnownHeadings` do not unintentionally modify legitimate content, especially nested headings or list markers.
- **Diff detection false positives:** Test `looksLikeRawDiffDump` against non-diff markdown containing similar numeric patterns.
- **Integration testing:** Ensure downstream rendering pipelines still produce the expected output after normalization.