

src/app/launchSequence.ts

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:44:01.603Z

Overview

`src/app/launchSequence.ts` is a new module that centralizes launch-flow constants and helper functions. It exposes a skip flag stored in `sessionStorage` and a `LaunchPhase` type for the boot, reveal, and ready stages.

Key changes

- **Constants**

- `LAUNCH_SESSION_KEY` (R1) = `"novadiff-launch-done-v1"` – identifies the skip flag.
- `LAUNCH_HOLD_MS` (R4) = 2400 ms – minimum time on the finished boot screen.
- `LAUNCH_HOLD_SKIP_AFTER_MS` (R6) = 900 ms – earliest moment the user can skip the hold.
- `LAUNCH_EXIT_FADE_MS` (R7) = 580 ms – fade duration when exiting the launch screen.
- `LAUNCH_REVEAL_MS` (R8) = 1200 ms – reveal animation duration.

- **Type**

- `LaunchPhase` (R10) – `"boot" | "reveal" | "ready"`.

- **Functions**

- `readLaunchSkipped()` (R12-R18) reads the flag from `sessionStorage`, returning `false` on error.
- `markLaunchComplete()` (R20-R26) writes `"1"` to `sessionStorage`, wrapped in a try/catch.

All symbols are exported for use by other parts of the application.

Impact

- Centralizes launch-related logic, reducing duplication across UI components.
- Safe access to `sessionStorage` prevents crashes on browsers that may throw.
- Timing constants can be tuned without modifying UI code.
- No external dependencies are introduced.

Risks & follow-ups

- **SessionStorage availability:** unknown from the available diff/scan evidence.
- **Race conditions:** unknown from the available diff/scan evidence.
- Unit tests for `readLaunchSkipped()` and `markLaunchComplete()` are recommended to cover error paths.