

src/app/llmStorage.ts

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:44:35.811Z

Overview

`src/app/llmStorage.ts` introduces LLM configuration types and persistence helpers.

Key changes

- **Imports** – `FileSummaryEvidence`, `DiffSelectionLineRange`, `DiffSelectionSymbolMatch`, `RiskSignal`, `SelectionDocMode` from `./types` (R1-R6).
- **Provider & settings** – `export type LlmProvider = "ollama" | "lmstudio"` (R9) and `export interface LlmSettings` with `provider`, `baseUrl`, `model` (R11-R15).
- **Payload** – `export interface LlmSummarizePayload` extends `LlmSettings` adds many fields for diff context and summarization metadata (R17-R62).
- **Defaults** – `defaultBase` and `defaultModel` return provider-specific URLs and model names (R66-R73).
- **Lifecycle** – `defaultLlmSettings` (R74-R80), `loadLlmSettings` (R82-R104) reads from `localStorage` key `novadiff_llm_settings_v1` with JSON parsing and fallbacks, and `saveLlmSettings` (R106-R108) writes the JSON string.

Impact

- Centralizes LLM configuration and persistence; future provider changes can be added in one place.
- Uses synchronous `localStorage` access; invoked during initialization or settings changes.

Risks & follow-ups

- **Environment safety** – `localStorage` may be unavailable in non-browser contexts; guard usage or provide fallback (unknown from the available diff/scan evidence).
- **JSON schema drift** – mismatched stored objects may silently default; ensure stored shape matches `LlmSettings`.
- **Provider defaults** – verify that `defaultBase` and `defaultModel` match actual server endpoints.
- **Type coverage** – extensive `LlmSummarizePayload` fields are not yet exercised; add unit tests for serialization/deserialization.