

src/app/selectedDiffDocs.ts

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:47:03.899Z

Overview

`src/app/selectedDiffDocs.ts` introduces a selection-context builder for diff views and several helper utilities.

Key changes

- **Imports** (lines 1-8): `DiffRow`, `DiffSelectionLineRange`, `DiffSelectionSymbolMatch`, `DiffSymbolSpan`, `FileDiffPayload`, `SelectionDocMode`.
- **Exported predicates** (lines 205-209): `isSelectableDiffRow(row)` and `isChangedDiffRow(row)`.
- **Interface** `SelectedDiffDocContext` (lines 213-225) defines the context returned by the builder.
- **Core builder** `buildSelectedDiffDocContext(payload, selectedIndices, requestedMode)` (lines 227-277) orchestrates selection analysis, symbol detection, excerpt generation, and key slugification.
- **Helper utilities:**
 - `buildLineRanges` (81-113) aggregates contiguous line ranges.
 - `findBestEnclosingSymbol` (145-170) selects the most relevant symbol.
 - `buildSelectionLabel` (172-187) creates a human-readable label.
 - `rowsForWindow` (65-80) and `buildExcerpt` (44-57) produce context excerpts.
 - `slugifySelectionKey` (196-203) normalizes the selection key.

Impact

- The builder now checks for empty payloads and non-selectable rows (lines 232-240).
- It chooses a symbol when available and sets `effectiveMode` accordingly (lines 243-245).
- Excerpts are capped at 10 k (exact) or 22 k (expanded) characters (lines 251-257).
- The selection key is slugified to a maximum of 80 characters (lines 261-263).

Risks & follow-ups

- Excerpt limits may truncate very large diffs; verify typical diff sizes. (unknown from the available diff/scan evidence)
- Truncation to 80 characters could cause key collisions; assess uniqueness. (unknown from the available diff/scan evidence)
- Symbol detection relies on `payload.left_symbols` / `right_symbols`; confirm these arrays are populated in all payloads. (unknown from the available diff/scan evidence)