

src/components/DocMermaidMount.tsx

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:53:10.103Z

Overview

A new React component `DocMermaidMount` is added to `src/components/DocMermaidMount.tsx` (lines 1-113). It renders Mermaid diagrams from a string definition, showing a loading skeleton, handling errors, and cancelling stale renders.

Key changes

- **Imports** (R1-R2): `useEffect`, `useRef`, `useState` from `react`; `runMermaidNodes` from `../app/mermaidBoot`.
- **RenderPhase type** (R4): `"idle" | "waiting" | "rendering" | "ready" | "error"`.
- **Props interface** (R6-R12): `definition: string`; optional `loading`, `loadingLabel`, `errorLabel`.
- **Component** (R14-R113):
 - Uses `useRef` for host `<div>` and a generation counter (`renderGenRef`).
 - `useEffect` on `[definition, loading]` handles empty definitions, shows skeleton, and triggers `runMermaidNodes([pre])` inside `requestAnimationFrame`.
 - Cancels outdated renders via `cancelled` flag and generation check.
 - UI renders a skeleton (`doc-mermaid-skeleton`), an error message (`doc-mermaid-error`), and a host `<div>` with classes reflecting the current phase.

Impact

- **Lifecycle safety:** Generation counter and cancellation guard prevent overlapping renders.
- **User feedback:** Skeleton and error UI provide clear status.
- **Styling hooks:** Class names (`doc-mermaid-mount`, `is-ready`, `is-busy`, `is-error`) allow CSS customization.

Risks & follow-ups

- **Race conditions:** Verify rapid `definition` changes do not trigger overlapping renders; the generation counter mitigates this.
- **CSS dependencies:** Ensure styles for the mentioned classes exist; missing styles could affect layout.
- **SSR compatibility:** Component uses `useEffect`, so it runs only on the client; confirm surrounding app handles this.
- **`runMermaidNodes` contract:** Import is used with `.then/.catch`; tests should cover success and failure paths.