

src/components/LlmSettingsModal.tsx

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:57:55.932Z

Overview

A new component `src/components/LlmSettingsModal.tsx` (lines 1-149) introduces a modal for configuring local LLM providers (Ollama or LM Studio). It exports `LlmSettingsModalProps` and internally manages provider, base URL, model, probe status, and busy state.

Key changes

- **Imports** (R1-4): `useEffect`, `useState` from React; types `LlmProvider`, `LlmSettings`; `saveLlmSettings`; `AnimatedOverlay`.
- **Props interface** (R6-10): `open: boolean`, `initial: LlmSettings`, `onClose: () => void`, `onSaved: (s: LlmSettings) => void`.
- **State** (R19-23): `provider`, `baseUrl`, `model`, `probe`, `busy`.
- **useEffect** (R25-32): resets state when `open` or `initial` changes.
- **Preset logic** (R34-42): `applyPreset` sets defaults for Ollama (`http://127.0.0.1:11434`, `llama3.2`) or LM Studio (`http://127.0.0.1:1234`, `local-model`).
- **UI** (R45-147): provider buttons, input fields, a test-connection button that calls `window.electronAPI?.llmProbe`, and a save button that persists settings via `saveLlmSettings` and triggers `onSaved`.

Impact

- **Performance:** All state updates are local to the modal; negligible overhead.
- **Maintainability:** Centralizes LLM configuration; adding new providers can reuse `applyPreset`.
- **Observability:** The `probe` message provides immediate feedback on connection tests.

Risks & follow-ups

- **Electron API availability:** The test button is disabled if `window.electronAPI?.llmProbe` is undefined; confirm this API is exposed in the renderer.
- **Prop validation:** Callers must supply a complete `initial LlmSettings`; missing fields could break state initialization.
- **CSS classes:** Ensure `llm-modal-backdrop`, `llm-modal`, etc., exist to avoid layout issues.
- **Persistence:** Verify that `saveLlmSettings` writes correctly and that `onSaved` updates parent state.