

## src/components/LlmSummaryMarkdown.tsx

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:58:51.429Z

### Overview

A new `src/components/LlmSummaryMarkdown.tsx` component is added to render LLM-generated markdown with GFM support, sanitization, and inline Mermaid chart rendering.

### Key changes

- **Imports:** added `react`, `react-markdown`, `rehype-sanitize`, `remark-gfm`, `normalizeGeneratedMarkdown`, and `runMermaidNodes`.
- **Props interface:** `LlmSummaryMarkdownProps` now requires a `source: string`.
- **MermaidBlock:** a memoized component that mounts a `<pre class="mermaid">` element and triggers `runMermaidNodes` in a `useEffect`.
- **LlmSummaryMarkdownInner:** normalizes the source via `useMemo`, renders `<ReactMarkdown>` with `remarkPlugins=[[remarkGfm]]` and `rehypePlugins=[[rehypeSanitize]]`, and customizes `a` and `code` components. Code blocks with `language-mermaid` are replaced by `MermaidBlock`.
- **Export:** `LlmSummaryMarkdown` is exported as `memo(LlmSummaryMarkdownInner)`.

### Impact

- **Correctness:** Markdown is sanitized and GFM-parsed, reducing XSS risk. Mermaid blocks are rendered client-side.
- **Maintainability:** All logic lives in a single component; memoization and `useMemo` keep re-renders minimal.
- **Performance:** `useMemo` normalizes only on source change; `memo` prevents unnecessary re-renders.
- **Observability:** `MermaidBlock` logs errors only if `runMermaidNodes` fails; otherwise silent.

### Risks & follow-ups

- **Sanitization:** Verify `rehypeSanitize` correctly strips dangerous tags; run integration tests with malicious input.
- **Mermaid rendering:** Ensure `runMermaidNodes` is available and handles errors; test with various chart sizes.
- **Dependency versions:** Confirm `react-markdown`, `rehype-sanitize`, and `remark-gfm` are compatible with the current React version.
- **Normalization:** `normalizeGeneratedMarkdown` must not alter essential markdown syntax; run unit tests on edge cases.