

src/components/launch/AppLaunchShell.tsx

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T05:13:38.871Z

Overview

A new component `src/components/launch/AppLaunchShell.tsx` is added to orchestrate the app launch sequence, providing a context, handling reduced-motion preferences, and managing phase transitions.

Key changes

- **Imports:** Adds React hooks (`useCallback` , `useEffect` , `useMemo` , `useState`) and launch-sequence utilities (`LAUNCH_REVEAL_MS` , `type LaunchPhase` , `markLaunchComplete` , `readLaunchSkipped`) plus `usePrefersReducedMotion` , `LaunchProvider` , `LaunchBoot` , and `launch.css` .
- **Props interface** (`AppLaunchShellProps` , lines 13-18): optional `chrome` , required `children` , optional `onPhaseChange` .
- **Component logic** (`AppLaunchShell` , lines 19-76):
 - Determines `skipSequence` via reduced-motion flag or persisted skip.
 - Manages `phase` (`boot` , `reveal` , `ready`) and `bootVisible` state.
 - Calls `markLaunchComplete` on boot exit and triggers `onPhaseChange` .
 - Provides context (`phase` , `skipSequence` , `brandReveal`) to descendants.
 - Computes motion-related CSS classes and renders `LaunchBoot` , optional chrome panel, and children.

Impact

- **Behavior:** Introduces a controlled launch flow that can skip the boot sequence if reduced motion is preferred or previously skipped.
- **UI:** Adds CSS classes (`is-launched` , `is-revealing` , `is-ready`) that affect visual transitions.
- **API:** Exposes `onPhaseChange` callback for external observers to react to phase changes.
- **Performance:** Adds a timeout (`LAUNCH_REVEAL_MS`) and state updates; negligible overhead but must be verified under heavy load.
- **Compatibility:** Requires `LaunchBoot` and `LaunchContext` to exist; missing imports will break the build.

Risks & follow-ups

- **Missing CSS:** Ensure `launch.css` defines the expected classes; otherwise transitions will be broken.
- **Reduced-motion handling:** Verify that `usePrefersReducedMotion` correctly propagates and that `readLaunchSkipped` persists state across sessions.
- **Phase callback:** Test that `onPhaseChange` is invoked exactly once per phase transition and that consumers handle it safely.

- **Context consumption:** Confirm that child components consume `LaunchProvider` correctly; otherwise they may receive undefined context values.