

src/components/launch/TypewriterText.tsx

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T05:15:09.559Z

Overview

A new component `src/components/launch/TypewriterText.tsx` implements a typewriter animation that respects the user's reduced-motion preference.

Key changes

- **Imports** (R1-R2): `useEffect`, `useRef`, `useState` from React and `usePrefersReducedMotion` from `../../app/usePrefersReducedMotion`.
- **Props interface** (`TypewriterTextProps`, R4-R15):
 - `text: string` – required.
 - Optional `active`, `persist`, `speed`, `delay`, `className`, `showCursor`, `onComplete`.
 - `persist` defaults to `true`; `speed` defaults to `22 ms`; `delay` defaults to `0`; `showCursor` defaults to `true`.
- **Component** (`TypewriterText`, R17-R99):
 - Uses refs (`onCompleteRef`, `completedRef`, `wasActiveRef`) to avoid stale closures.
 - When `active` is false, resets visibility unless `persist` is true and the animation has finished.
 - If the user prefers reduced motion (`reduced`), the full text is shown immediately and `onComplete` is called.
 - Otherwise, a `setTimeout` / `setInterval` loop reveals characters at `speed` ms per character, clearing timers on cleanup.
 - Renders a `<span>` containing the visible slice of `text` and, if typing is in progress, a cursor element (`typewriter-cursor`).

Impact

- Adds a self-contained typewriter effect with optional persistence and completion callback.
- Requires React 16.8+ for hooks and the `usePrefersReducedMotion` hook.
- No global state or external dependencies beyond React.

Risks & follow-ups

- Verify that `usePrefersReducedMotion` correctly detects system settings; test both reduced and normal modes.
- Ensure cleanup logic (`cancelled`, `clearTimeout`, `clearInterval`) prevents leaks when `active` toggles rapidly.
- Confirm that `persist` keeps the text visible after completion when `active` becomes false.
- Test cursor rendering logic with `showCursor`, `active`, `reduced`, and `done` flags to avoid flicker.