

vite.config.ts

Kind: added · Baseline: a9c34bfb03fe · Target: NovaDiff · Generated: 2026-05-20T04:11:23.370Z

Overview

A new `vite.config.ts` (lines 1-49) bootstraps the NovaDiff dev server. It imports Vite helpers, React and Tailwind plugins, and sets up path resolution, aliases, server options, and dependency optimization.

Key changes

- **Imports**
 - `import path from "node:path";` (R1)
 - `import { defineConfig } from "vite";` (R2)
 - `import react from "@vitejs/plugin-react";` (R3)
 - `import tailwindcss from "@tailwindcss/vite";` (R4)
- **Root resolution**
 - `const repoRoot = path.resolve(__dirname);` (R6) – used for watch-ignore paths.
- **Export**
 - `export default defineConfig(() => ({ ... }));` (R9) – Vite configuration.
- **Aliases**
 - `@novadiff/graph-core` → `packages/graph-core/src` (R15)
 - `@novadiff/graph-view` → `packages/graph-view/src` (R16)
- **Server**
 - `port: 1420`, `strictPort: true`, `host: "127.0.0.1"` (R20-22)
 - Extensive `watch.ignored` patterns (R26-35) to avoid reloads on generated artifacts.
- **OptimizeDeps**
 - Pre-bundles `@xyflow/react`, `zustand`, `d3-force`, `@dagrejs/dagre`, `graphology`, `elkjs/lib/elk.bundled.js` (R39-46)
 - Marks `elkjs` for interop (R47).

Impact

- **Developer experience** – `clearScreen: false` keeps console logs visible; `strictPort` prevents silent port fallback.
- **Performance** – `optimizeDeps` speeds up dev builds by pre-bundling heavy libraries.
- **Observability** – Watch-ignore list reduces unnecessary reloads, keeping the dev server responsive.

Risks & follow-ups

- Verify that `repoRoot` resolves correctly on all CI environments; failing to do so may break ignored paths.
- Ensure port 1420 is available; otherwise Vite will error due to `strictPort: true`.

- Confirm that the alias paths match the actual package locations; mismatches will cause import failures.
- Test that the `optimizeDeps` list covers all runtime dependencies; missing entries could lead to slower hot-reloads.