

Table 1: Real-robot corn-to-plate results using a Piper arm and two D455 cameras. Both methods use the same undertrained 5k $\pi_{0.5}$ base policy and identical execution settings; ASRR uses a 1000-epoch output-space refiner with $\alpha = 1.5$. Each placement contains 20 trials per method, and Overall aggregates 80 trials. Round statistics report mean $\pm$ sample standard deviation over four 20-trial rounds.

Method	Left upright	Left tilted	Right upright	Right tilted	Overall	Round rate (%)
$\pi_{0.5}$ 5k Base	12/20 (60%)	14/20 (70%)	12/20 (60%)	5/20 (25%)	43/80 (53.8%)	53.8 ± 6.3
$\pi_{0.5}$ 5k + ASRR	13/20 (65%)	16/20 (80%)	15/20 (75%)	5/20 (25%)	49/80 (61.3%)	61.3 ± 11.1
Gain (pp)	+5	+10	+15	0	+7.5	+7.5

Table 2: Raw real-robot results over four evaluation rounds per method. Each placement column contains five trials, for a total of 20 trials per round.

Method	Round	Left upright	Left tilted	Right upright	Right tilted	Total
$\pi_{0.5}$ 5k Base	Base-1	4/5	3/5	4/5	1/5	12/20
	Base-2	3/5	4/5	3/5	1/5	11/20
	Base-3	3/5	3/5	3/5	2/5	11/20
	Base-4	2/5	4/5	2/5	1/5	9/20
$\pi_{0.5}$ 5k + ASRR	ASRR-1	3/5	3/5	3/5	1/5	10/20
	ASRR-2	4/5	3/5	3/5	3/5	13/20
	ASRR-3	2/5	5/5	4/5	0/5	11/20
	ASRR-4	4/5	5/5	5/5	1/5	15/20