

Temporal Score Incomparability in LLM Benchmarks: A Large-Scale Psychometric Audit of 5,227 Models

Anonymous ACL submission

Abstract

Large language model (LLM) benchmark scores are routinely compared across model generations, yet whether individual items measure the same construct over time is rarely tested. We apply differential item functioning (DIF) analysis from educational measurement to the METABENCH response matrix (5,227 models across six benchmarks), validated through semi-synthetic injection with a cross-subject matching guarantee. Between 2023 and 2024 model cohorts, 18–31% of items exhibit large temporal DIF—orders of magnitude above random baselines—while aggregate rankings remain near-perfect ($\rho \geq 0.994$). DIF flags are near-independent of web-overlap contamination labels, revealing that global exposure and differential functioning are complementary diagnostic dimensions. Base and instruct models exhibit opposite DIF directions, confirming structured capability shifts beyond contamination. We propose a three-step Monitor/Triage/Correct audit protocol with empirically grounded thresholds for benchmark maintainers. LLM benchmarks need psychometric monitoring, not just score reporting.¹

1 Introduction

When we say “Model B outperforms Model A on MMLU,” we implicitly assume that the benchmark measures the same construct in the same way for both models. This assumption of temporal comparability underpins every cross-generation comparison published on leaderboards and in model reports, yet it is rarely tested. We use *measurement invariance* to denote the property that test items function identically across groups (Meredith, 1993), *differential item functioning* (DIF) as the item-level statistical test for violations, and *temporal score incomparability* (measurement

non-invariance across temporal cohorts, manifesting as score incomparability) as the empirical phenomenon when DIF is detected—scores are not directly comparable across cohorts because item measurement properties differ systematically, without implying degradation or attributing cause. Applying Mantel-Haenszel DIF analysis (Holland and Thayer, 1988) with Educational Testing Service (ETS) severity classification to the METABENCH response matrix (Kipnis et al., 2024), we find that 31% of Massive Multitask Language Understanding (MMLU) (Hendrycks et al., 2021) items receive ETS Category C classification ($|\Delta_{MH}| \geq 1.5$, $p < 0.05$) between 2023 and 2024 model cohorts—versus 0.62% under a random-split control. Aggregate rankings are robust ($\rho \approx 0.997$), but absolute scores are not directly comparable: DIF-corrected scoring (excluding all C-flagged items) shifts accuracy by +2.12 pp on average, with individual models displaced by up to 851 rank positions. This instability does not invalidate the benchmark—aggregate rankings are massively redundant—but it is diagnostic, revealing which capability dimensions shift across model generations.

Existing approaches to benchmark integrity focus on *global exposure*—whether items appear in training corpora—through membership inference (Shi et al., 2024) and performance-based detection (Dekoninck et al., 2024; Liang, 2026; Tao et al., 2026), validated against web-overlap labels (Li et al., 2024). Whether benchmark items function equivalently across model generations—*measurement invariance*—has not been systematically examined (Figures 1 and 2). We find these two signals are near-independent (Jaccard = 0.206, $\phi = 0.012$): complementary diagnostic dimensions, not competing ones.

We apply a temporal DIF audit framework to the full METABENCH response matrix (5,227 models $\times$ 12,508 MMLU items), to our knowledge the largest-scale DIF analysis on LLM benchmarks,

¹Code and data: https://github.com/anonymous-nlp-2026-2/irt_equated_benchmark




Figure 1: Four-stage psychometric auditing pipeline. ① A binary response matrix records model correctness across benchmark items, with models split into temporal cohorts (2023 reference vs. 2024 focal). ② Models are stratified into $K=5$ score quintiles. ③ Per-item Mantel-Haenszel DIF tests compute Δ_{MH} across strata. ④ ETS classification assigns severity labels (A/B/C). Result: 29.2% of items flagged as C, yet stable-item $\rho = 0.997$, replicated across six benchmarks.

complementing concurrent work on anchor-item calibration (Habba et al., 2026) and addressing the fragility of existing detectors under post-training perturbation (Wang et al., 2026). Two structural controls, a sensitivity check, and replication across all six METABENCH benchmarks confirm that the temporal DIF rate (29.2% after non-independence correction; 17.9–31.3% across benchmarks) is not a methodological artifact (Sections 4.2, 4.4 and 4.7). We make three contributions:

1. **Temporal DIF at scale:** 29.2% of MMLU items exhibit temporal DIF (17.9–31.3% across six benchmarks), near-independent of web-overlap labels (Jaccard = 0.206); base-vs-instruct stratification reveals opposite patterns ($\chi^2 = 562.7$), confirming mechanism separation (Sections 4.2, 4.3, 4.7 and 5.1).
2. **Cross-subject matching with $\Delta\text{FPR} = 0$ guarantee:** solves matching-variable corruption under single-subject contamination, extending to $k \leq 5$; complemented by design effect (DEFF) correction and semi-synthetic validation (Section 4.5).
3. **Actionable audit protocol:** a three-step Monitor/Triage/Correct protocol with empirically grounded thresholds (Section 5.2).

2 Related Work

Psychometric Methods for LLM Evaluation. The Mantel-Haenszel procedure (Holland and Thayer, 1988) remains the most widely used DIF detector in educational testing due to its simplicity and well-characterized statistical properties, operating nonparametrically without requiring an explicit item response theory (IRT) model. DIF analysis is a specific instance of measurement invariance testing (Meredith, 1993), which examines whether an instrument functions equivalently across groups. IRT adoption in LLM evaluation has accelerated since Lator et al. (2019) introduced it to natural language processing: recent work calibrates test sets for discriminability, item selection, and adaptive evaluation. The closest concurrent work is Growing Pains (Habba et al., 2026), which uses parametric IRT (two-parameter logistic [2PL] / three-parameter logistic [3PL] fixed-parameter calibration) to equate scores across temporal cohorts. MH-DIF is nonparametric and robust to model misspecification—an advantage given poor 2PL fit for MMLU (root mean square error of approximation [RMSEA] > 0.08 ; Section A.2). Growing Pains prescribes how to equate scores after instability is detected; our work diagnoses *which* items exhibit instability and quantifies severity via

ETS classification, providing pre-screened anchor candidates for downstream equating. Their anchor-item selection can directly consume our stable-item set; our finding that 31% of items exhibit temporal DIF identifies which items should *not* serve as anchors. To our knowledge, no prior work applies DIF to benchmark temporal comparability.

Contamination Detection. A growing family of methods detects benchmark contamination through model behavior or training-data analysis. Membership inference approaches use token-level log-likelihood statistics (Shi et al., 2024) or statistical anomalies (Dekoninck et al., 2024) to flag items likely seen during training. A standard validation practice is to compare detector output against web-overlap labels (Li et al., 2024), which classify items based on verbatim matches in publicly accessible corpora. Such labels measure *global exposure*—whether an item exists in training data—rather than *differential item functioning*: whether an item behaves differently across model cohorts. This global-vs-differential distinction motivates our comparison with web-overlap labels (Section 4.3). Wang et al. (2026) show that existing contamination detectors are fragile under reinforcement learning, further motivating behavioral approaches grounded in psychometric theory.

Benchmark Quality and Design. Meta-evaluation of static benchmark quality (Zhu et al., 2026) assesses properties at a single snapshot; our temporal DIF analysis diagnoses *when* measurement properties shift. Work on LLM memorization (Carlini et al., 2023) establishes that memorization depends on data frequency and model scale, reinforcing the distinction between global exposure and differential behavior. MMLU-CF (Zhao et al., 2025) reconstructs contamination-free items without replacement; DIF monitoring identifies which existing items remain measurement-invariant. Dynamic benchmarks (Kiela et al., 2021) mitigate contamination by construction but lack psychometric equating. Broader surveys (Chang et al., 2024) identify benchmark saturation as a systemic challenge that DIF analysis directly addresses.

3 Method

We adopt Differential Item Functioning (DIF) analysis from educational measurement to assess whether individual benchmark items behave consistently across groups of LLMs. The procedure




Figure 2: Global vs. differential contamination via Item Characteristic Curves (ICCs). **Left:** global contamination produces no DIF; both cohorts encounter the item, and their ICCs overlap. **Right:** differential contamination produces DIF; the focal cohort’s ICC shifts due to disproportionate exposure. The enrichment ratio of ≈ 1.0 between DIF flags and web-overlap labels is expected because most items fall into the left category.

requires only a binary response matrix and group labels, with no access to model internals or training data. Below we define the data, the statistical test, the cohort designs, and a semi-synthetic validation framework.

3.1 Data

The primary dataset is the METABENCH response matrix (Kipnis et al., 2024), which records binary outcomes (1 = correct, 0 = incorrect) for 5,227 models evaluated on 12,508 MMLU items (Hendrycks et al., 2021). Models span release dates from 2023 to 2024, drawn from the Open LLM Leaderboard. MMLU covers 57 subjects grouped into five broad domains (STEM, Humanities, Social Sciences, Other, and a mixed category). We supplement the response matrix with the web-overlap contamination labels of Li et al. (2024), which classify 9,229 of 12,508 items (73.8% coverage) as “contaminated” or “clean” based on verbatim matches in publicly accessible web corpora. These labels serve as an external reference for evaluating the relationship between DIF flags and existing contamination indicators.

3.2 Mantel-Haenszel DIF and ETS Classification

In educational testing, Differential Item Functioning (DIF) occurs when an item’s statistical relationship to the latent trait θ differs between two groups after conditioning on ability level. An item with DIF is not merely harder for one group; it functions differently relative to what the group’s overall ability would predict. The standard terminology refers to test-takers as “examinees” and questions

as “items.” In our setting, examinees are LLMs and items are benchmark questions.

The Mantel-Haenszel (MH) procedure (Holland and Thayer, 1988; Magis et al., 2010) detects DIF by stratifying examinees into K score bins based on total score (a proxy for θ) and computing a common odds ratio across strata. We use $K = 5$ equiprobable strata (quintile-based binning) following ETS recommended practice for large-scale assessments (Donoghue and Allen, 1993; Clauser and Mazor, 1998). Within each stratum k , the responses of the reference group and the focal group form a 2×2 contingency table:

$$\alpha_{\text{MH}} = \frac{\sum_{k=1}^K A_k D_k / T_k}{\sum_{k=1}^K B_k C_k / T_k}, \quad (1)$$

where A_k and B_k are the number of correct and incorrect responses in the reference group for stratum k , C_k and D_k are the corresponding counts for the focal group, and T_k is the total number of examinees in stratum k . Under the null hypothesis of no DIF, $\alpha_{\text{MH}} = 1$. The log odds ratio is converted to the ETS delta scale:

$$\Delta_{\text{MH}} = -2.35 \ln(\alpha_{\text{MH}}). \quad (2)$$

The Educational Testing Service (ETS) classifies DIF severity into three categories based on $|\Delta_{\text{MH}}|$. Category A (negligible) requires $|\Delta_{\text{MH}}| < 1.0$. Category C (large) requires both $|\Delta_{\text{MH}}| \geq 1.5$ and statistical significance at $p < 0.05$ from the MH chi-squared test. Category B (moderate) includes all remaining items: those with $1.0 \leq |\Delta_{\text{MH}}| < 1.5$, or $|\Delta_{\text{MH}}| \geq 1.5$ without statistical significance. The dual threshold in ETS C (effect size and significance) guards against flagging items that show large but unreliable effect sizes. These thresholds were calibrated for human test-taker populations; we retain them as standardized reference points and verify robustness across stricter cutoffs (Section 4.2). Throughout this paper, we report the percentage of items classified as ETS C, denoted C%. At $N = 1,887$ (the temporal comparison; 5,227 total across all cohort designs), significance ($p < 0.05$) is nearly automatically satisfied for any $|\Delta_{\text{MH}}| \geq 1.5$: only 3 of 3,918 C items lack significance, so the dual criterion effectively reduces to a single effect-size threshold; per-item DEFF

correction (Section D) restores p -value selectivity by reducing effective N : under simple-mean DEFF, 269 items (6.9%) lose significance while retaining $|\Delta_{\text{MH}}| \geq 1.5$; 74% of these are near-miss ($p_{\text{adj}} \in [0.05, 0.10]$).

The choice of matching variable (the total score used for stratification) affects both validity and interpretation. We distinguish three matching strategies: (1) *standard matching* uses the within-benchmark total score on all items of the same benchmark; (2) *cross-subject matching*, adapting purified subtest matching (Swaminathan and Rogers, 1990) to the LLM multi-subject setting, uses the total score on all subjects *other than* the one containing the item under test, preventing the matching variable from absorbing injected contamination signals (Section 3.4); and (3) *external matching* uses the total score on a different benchmark entirely (e.g., MMLU total score as the matching variable when testing DIF on Grade School Math 8K (GSM8K) items), providing an independent ability proxy uncontaminated by the target benchmark. Cross-subject and external matching both address matching variable contamination but at different granularities: cross-subject operates within a multi-domain benchmark, while external operates across benchmarks. Total score matching is adequate: IRT θ correlates at $r = 0.9986$ with total scores (Section 4.4).

LLM-specific challenges. Applying MH-DIF to LLMs introduces four challenges absent in educational testing. First, overlapping training corpora violate local independence; permutation simulation (1,000 replications shuffling group labels within score strata) confirms local-dependence-attributable FPR inflation < 0.001 pp under cross-subject matching (Section A). Second, fine-tuned variants within model families are not independent examinees; graduated de-duplication shows family structure does not inflate C% (Section 4.4). Third, bimodal ability distributions motivate quintile-based stratification. Fourth, MMLU’s 57-subject structure raises a multidimensionality concern (Ackerman, 1992; Roussos and Stout, 1996): domain-level ability profiles are nearly flat across cohorts (Cohen’s d range = 0.12), cross-subject and within-subject matching agree ($\kappa = 0.80$, 834 items), and cross-subject-unique C items do not concentrate in high-shift subjects (Section C).

3.3 Cohort Designs

We construct five cohort comparisons: (1) *Temporal*: 2023 ($N = 1,080$) vs. 2024 ($N = 807$) models, the primary comparison; (2) *Ability-quintile*: Q1–Q2 vs. Q4–Q5 within the same temporal window; (3) *Within-family*: Llama-2 ($N = 161$) vs. Llama-3 ($N = 308$), isolating generational changes within a single family; (4) *Within-subject*: per-subject DIF to test domain concentration; and (5) *Random split*: two random halves of the 2023 cohort ($N = 540$ each) as a sanity check. Calendar-year boundaries are coarse; half-yearly comparison ($C\% = 34.4\%$; Section E) and base-only/instruct-only analyses ($C\% = 32.1\%/36.5\%$; Section O) confirm DIF persists under finer slicing.

3.4 Semi-Synthetic Injection Framework

We use contamination injection as a controlled case study to validate DIF detection power; DIF itself is mechanism-agnostic and flags items that function differently without attributing cause (Section 5.2). To evaluate whether MH-DIF can detect differential contamination when it is present, we construct a semi-synthetic framework with controlled ground truth.

Procedure. From items classified as ETS A in the uninjected data (negligible DIF), we select 20% uniformly at random as the “contaminated” set. For each contaminated item, we flip incorrect responses to correct in the focal group at exploitation rate $p \in \{0.0, 0.3, 0.5, 0.7, 1.0\}$. We then run MH-DIF on the modified response matrix and measure detection performance. We report $\Delta\text{TPR} = \text{TPR}(\text{injected}) - \text{TPR}(\text{baseline})$ and $\Delta\text{FPR} = \text{FPR}(\text{injected}) - \text{FPR}(\text{baseline})$, where TPR is the true positive rate on injected items and FPR is the false positive rate on uninjected items. Each injection level is repeated across 5 random seeds for uncertainty estimation. Because binary response flipping represents a stylized uniform injection pattern, reported ΔTPR values may overestimate detection power; realistic contamination (partial memorization, format-specific advantages) would produce weaker signals.

Cross-subject matching. The choice of matching variable is critical for valid semi-synthetic evaluation. When contamination is injected into items within subject X , the total score on subject X absorbs part of the injection signal. Using this contaminated total score as the MH matching variable

violates the conditional independence assumption and inflates FPR. Cross-subject matching resolves this by computing the matching variable from all subjects *other than* the one being tested.

Remark (Zero FPR under single-subject matching). Let $M_i^{(-s)} = \sum_{j \neq s} Y_{ij}$ be the matching variable for examinee i on focal subject s . Under single-subject injection (contamination confined to subject s), the tested item belongs to s and does not contribute to $M_i^{(-s)}$; injecting contamination into s leaves $M_i^{(-s)}$ unchanged. Therefore $\Delta\text{FPR} = 0$ by construction.

When contamination spans multiple subjects simultaneously, $M_i^{(-s)}$ may absorb signal from other contaminated subjects, potentially inflating FPR. Empirically, this guarantee extends to multi-domain contamination affecting $\leq 9\%$ of subjects ($k \leq 5$), with graceful degradation beyond this boundary (Section 4.5).

Empirically, $\Delta\text{FPR} = 0.000$ across all five MMLU domains (bootstrap 95% CI = $[0.000, 0.000]$). $\Delta\text{FPR} = 0$ is a constructive guarantee of the matching strategy, independent of injection realism, whereas ΔTPR may overestimate detection power under the stylized uniform injection. ΔFPR remains negligible for single-domain contamination ($k \leq 5$); when contamination spans many domains, within-subject matching should be preferred (Section 4.5). We adopt cross-subject matching as the standard protocol.

Following DIF convention (Wainer and Braun, 1993), we do not apply family-wise error correction: the dual ETS C threshold ($|\Delta_{\text{MH}}| \geq 1.5$ and $p < 0.05$) guards against false positives; Benjamini-Hochberg false discovery rate correction at $q = 0.05$ reclassifies only 3 of 3,918 C items (Section A). Diagnostic procedures (Yen’s Q3, domain-specificity, DIF decomposition) and further details appear in Section A.

4 Experiments

We apply MH-DIF to the METABENCH response matrix (Kipnis et al., 2024) (5,227 models $\times$ 12,508 MMLU items (Hendrycks et al., 2021)), with temporal cohorts defined by release date (2023 vs. 2024). Cross-benchmark validation across all six METABENCH benchmarks appears in Section 4.7.




Figure 3: Semi-synthetic dose-response for DIF detection on MMLU. ΔTPR ($= \text{TPR}_{\text{injected}} - \text{TPR}_{\text{baseline}}$) increases monotonically with exploitation rate p under binary injection (a calibration upper bound; Section 3.4); MH-DIF is sensitive to differential item behavior when present. Baseline (no injection) produces $\Delta\text{TPR} \approx 0$.

4.1 Validation: DIF Detection Power

A Monte Carlo power analysis (1,000 replications) using empirical 2PL parameters from PSN-IRT (Zhou et al., 2026) ($\bar{a} = 1.2$, $\bar{b} = -0.84$) confirms that at $N \geq 100$ per cohort, ETS C achieves TPR of 0.68–0.80 (under uniform injection) and area under the curve (AUC) of 0.93–0.94 for $|\Delta_{\text{MH}}| \geq 1.4$ (Section A). Our temporal cohorts ($N_{\text{ref}} = 1,080$, $N_{\text{focal}} = 807$) far exceed this threshold; power varies with item discrimination (TPR 0.40–0.95 across $a = 0.5$ –2.0; Section A.2).

4.2 Temporal DIF: ~29% of Items Exhibit Differential Functioning

We compare 2023 ($N = 1,080$) against 2024 ($N = 807$) models; 31.3% of items receive ETS C classification ($|\Delta_{\text{MH}}| \geq 1.5$; bootstrap 95% CI: [29.2%, 37.8%]; family-level cluster bootstrap: [26.7%, 53.2%]; Section E). Two DEFF estimators bound the non-independence effect: simple-mean DEFF yields 29.2% and weighted-mean yields 13.5%, bracketing C% at 13.5–29.2%; the cluster bootstrap CI excludes the weighted-mean estimate, providing model-independent evidence that over-correction drives the lower bound (Sections D, I and L). Random

Table 1: DIF landscape across cohort definitions. ETS C denotes the percentage of items with $|\Delta_{\text{MH}}| \geq 1.5$. C% (web-clean) is the DIF-C flagging rate among items classified as web-clean by Li et al. (2024). Enrichment is the ratio of observed to expected overlap between DIF flags and web-overlap labels. Dashes (–) indicate comparisons where Li et al. labels are not applicable.

Cohort Definition	$N_{\text{ref}} / N_{\text{focal}}$	C%	C% (web-clean)	Enrich.
Temporal (2023 vs. 2024)	1,080 / 807	31.3	0.318	0.964
Ability quintile (Q1–2 vs. Q4–5)	$\sim 2,090 / \sim 2,090$	2.9	0.027	1.19
Within-family (Llama-2 vs. 3)	161 / 308	61.3	–	–
Random split 2023 (sanity)	540 / 540	0.62	–	–
Random split 2024 (sanity)	$\sim 400 / \sim 400$	1.3	–	–
Within-subject (avg, 5 subj.)	varies	38.1	–	–

permutations within the 2023 cohort confirm the ETS C threshold maintains per-item FPR below 1% (99th percentile $|\Delta_{\text{MH}}| = 1.45$); no non-dominant family drives the signal (leave-one-family-out [LOFO] $|\Delta\text{C\%}| \leq 2.93$ pp; Table 8 and section J).

Three controls confirm genuine temporal change (Table 1): random splits yield mean C% of 0.62% (2023; 100 permutations) and 1.3% (2024; 100 permutations), 24–50 $\times$ below temporal C%; ability-quintile comparison yields 2.9%; and 1:1 nearest-neighbor matching on total score ($N=638/\text{group}$, Cohen’s $d = -0.17$) yields C% = $28.9\% \pm 0.1\%$; at most ~ 2.4 pp is attributable to ability mismatch ($p < 0.01$; Section A).

Across all 57 subjects, C% ranges from 20.7% to 48.4% (mean $\approx 30\%$; Table 1). DIF rates are domain-invariant (Kruskal-Wallis $p = 0.78$), but DIF *direction* exhibits domain dependence: STEM items favor 2024 models (55.4%), Humanities favor 2023 (64.4%). DIF is item-specific: domain-level accuracy gains explain $< 0.1\%$ of item-level DIF variance (Section C). A difficulty–direction interaction emerges ($r = -0.597$): 2024 models gain on hard items while eroding on easy ones. The temporal DIF finding persists across thresholds (18.4% at $|\Delta_{\text{MH}}| \geq 2.0$, 10.2% at ≥ 2.5).

4.3 Comparison with Web-Overlap Labels

Direct comparison of DIF flags against the web-overlap labels of Li et al. (2024) on 9,229 annotated items shows near-independence (enrichment = 0.964, Jaccard = 0.206; $p = 0.88$; Table 1 and section C): DIF-C rates are 30.7% among web-contaminated items and 31.8% among clean items. Because web-overlap labels are a proxy for training-set membership (based on verbatim web matches, not actual training corpora), this near-independence could partly reflect proxy noise. Crucially, label-independent evidence confirms




Figure 4: Ranking degradation under DIF-ordered vs. random item removal. DIF-ordered removal (orange) degrades ρ faster than random (blue band = mean $\pm$ 1 SD, 20 seeds). Dashed lines: Monitor/Flag (15%) and Flag/Act (25%) thresholds (Section 5.2).

mechanism separation: base and instruct models exhibit opposite DIF directions ($\chi^2 = 562.7$; Section 5.1), a reversal incompatible with uniform contamination. Semi-synthetic injection confirms detection power ($\Delta\text{TPR} = +0.508$ at $p = 0.5$; Figure 3). Web-overlap labels measure *global exposure*, while DIF measures *differential functioning*—complementary diagnostic dimensions (Figure 2).

4.4 Structural Analysis

Two structural controls and a sensitivity check fail to reduce temporal C% below 31% (Table 5): matched-ability quintiles, within-subject DIF (C% = 38.1%; cross-subject C% is more conservative due to lower local dependence), and IRT θ -conditioning ($r(\theta, \text{total score}) = 0.9986$). Logistic regression detects an additional 17.7% with non-uniform DIF ($|\beta_{\text{interaction}}| \geq 0.5$), reaching a union of 47% (Section C). Ability-matched C% converges to ~ 28 –29% for both temporal and within-family comparisons despite vastly different unmatched rates (Section C).

4.5 Detection Power under Controlled Injection

Cross-subject matching achieves $\Delta\text{FPR} = 0.000$ across all five MMLU subjects (4/5 with $\Delta\text{TPR} > 0.3$ at $p = 0.5$; Section 3.4), while within-subject matching inflates FPR by +0.186 (Figure 5). The $\Delta\text{FPR} \approx 0$ guarantee holds for




Figure 5: Cross-subject vs. within-subject matching for semi-synthetic DIF detection. Cross-subject matching eliminates FPR inflation ($\Delta\text{FPR} = 0.000$) while preserving detection power ($\Delta\text{TPR} > 0.3$ for 4/5 subjects at $p = 0.5$). Within-subject matching inflates FPR by +0.186 on average.

$k \leq 5$ contaminated subjects ($\Delta\text{FPR} < 0.007$); at $k=20$, ΔFPR rises to 0.167—still insufficient to account for the observed 31% C% (Table 7). Difficulty-dependent injection yields $\Delta\text{TPR} \approx 0.41$ at $p = 0.5$ (vs. 0.51 uniform), bounding overestimation at $\sim 20\%$ (Section A).

4.6 Downstream Impact

Stable-item ranks are preserved across all six benchmarks (mean $\rho = 0.997$, mean $\tau = 0.962$; flip rate $\leq 2.9\%$; Table 2). DIF-flagged items concentrate discriminative signal: DIF-ordered




Figure 6: Downstream impact of DIF-based item filtering on model rankings. Despite $\rho \approx 0.997$ overall, individual model families show systematic rank shifts when evaluated on stable items (non-C-flagged) only.

Table 2: Temporal DIF across six METABENCH benchmarks (2023 vs. 2024 cohorts). ρ/τ : rank correlation between full and stable-item rankings; Flip: pairwise rank-flip rate; Ratio: C%/random baseline.

Benchmark	Items	C%	ρ	τ	Flip%	Rand. C%	Ratio
MMLU	12,508	31.3	0.9965	0.9600	2.00	0.62	50×
WinoGrande	1,267	30.3	0.9943	0.9432	2.84	0.32	95×
TruthfulQA	817	29.7	0.9971	0.9586	2.07	0.37	80×
ARC	1,172	26.9	0.9962	0.9538	2.31	0.60	45×
GSM8K	1,319	18.9	0.9993	0.9843	0.78	0.30	63×
HellaSwag	10,042	17.9	0.9986	0.9722	1.39	0.28	64×

removal degrades ρ faster than random removal across all six benchmarks (Figure 4; $z = -8$ to -49 ; Figure 6). Removing C-flagged items disproportionately disadvantages 2024 models (cohort gap = 96.2 positions, 40× random; $p < 0.001$); DIF-corrected scoring shifts accuracy by +2.12 pp on average (Sections K and M).

4.7 Cross-Benchmark Validation

Temporal DIF extends across all six METABENCH benchmarks (Table 2): C% ranges from 17.9% (HellaSwag (Zellers et al., 2019)) to 31.3% (MMLU), with knowledge/reasoning benchmarks—including ARC (AI2 Reasoning Challenge)—consistently higher than procedural ones (C% = 26.9–31.3% vs. 17.9–18.9%). These differences may partly reflect item difficulty distributions; we treat them as descriptive.

Semi-synthetic injection on GSM8K confirms detection power ($\Delta\text{TPR} = +0.514$; Section F and fig. 7).

5 Discussion

5.1 Temporal DIF as Structured Signal

Temporal DIF detects *that* items function differently across cohorts, not *why*—by design (Section 3.3). Stratifying by model type reveals opposite patterns: base models ($N=1,409$) are 60.1% reference-favoring ($r = -0.570$), while instruct models ($N=478$) are 65.6% focal-favoring ($\chi^2 = 562.7$, $p < 10^{-124}$). This reversal reflects structured item-level bias rather than uniform group impact (Camilli and Shepard, 1994), validating DIF as a mechanism-agnostic diagnostic (Section B). Composition downsampling ($\Delta = 1.08$ pp) and base-only/instruct-only analyses confirm DIF is not an artifact of cohort structure (Sections N to P).

Three features distinguish LLM temporal DIF from educational settings: (1) C% (29.2%; cluster bootstrap CI: [26.7%, 53.2%]) substantially exceeds typical rates (Clauser and Mazor, 1998); (2) DIF flags and web-overlap labels are near-independent (Jaccard = 0.206); (3) the base/instruct reversal (odds ratio [OR] = 4.75; Section B) favors a broader-signal reading over distinct-construct independence.

5.2 Recommended DIF Audit Protocol

Item-level properties do not predict DIF susceptibility (area under the ROC curve [AUROC] = 0.60; Section H), precluding pre-screening. We recommend: (1) *Monitor*—run MH-DIF audits when ≥ 500 models accumulate, triggering review when C% exceeds 20× the random-split baseline; (2) *Triage*—DIF × web-overlap co-occurrence warrants removal, DIF on web-clean items warrants monitoring; (3) *Correct*—expert review, not automatic removal (Camilli and Shepard, 1994; Penfield and Camilli, 2007) (Section M).

6 Conclusion

Across six benchmarks, 17.9–31.3% of items exhibit temporal DIF while rankings remain stable ($\rho \geq 0.994$); base-vs-instruct reversals and web-overlap independence confirm signal beyond contamination.

Limitations

Three primary limitations apply. (1) The semi-synthetic framework uses uniform binary response flipping, a stylized injection model; reported Δ TPR values may overestimate detection power. Partial memorization scenarios—where models recall item cues without deterministic answer flipping—would produce weaker and qualitatively different DIF patterns than our binary injection model. The framework detects *that* items function differently but not *why*: multiple exclusion analyses (ability matching, web-overlap comparison, item-quality annotation) narrow the space of explanations but do not isolate a single mechanism; the specific training factors driving temporal DIF remain unidentified. Follow-up expert review is needed to determine whether flagged items should be retired or retained. (2) The MH χ^2 test assumes independent examinees; LLM model families violate this assumption. Two DEFF estimators (13.5–29.2%) and family-level cluster bootstrap (95% CI: [26.7%, 53.2%]) bound the impact, but the extreme relatedness of some families (e.g., hundreds of Llama-2 fine-tunes) exceeds the clustering levels studied in educational settings (French and Finch, 2010).

(3) Cross-subject matching assumes contamination affects a minority of domains; Δ FPR rises to 0.167 when contamination spans ≥ 20 subjects. Although composition control experiments show a small residual shift ($\Delta = 1.08$ pp; Section P), base/instruct ratio changes between cohorts remain a potential confound that cannot be fully eliminated without single-architecture longitudinal data. Temporal cohorts defined by calendar year provide coarse granularity, and generalizability to partial-credit and free-form generation benchmarks is untested. Multidimensional DIF (Ackerman, 1992) may arise when MMLU’s 57 subjects span distinct latent dimensions; cross-subject matching mitigates between-domain multidimensionality but not within-domain violations. IRT parameters are used only for auxiliary power analysis; all core DIF results are nonparametric. Additionally, model release dates need not align with training-data cutoff dates, and generalization beyond multiple-choice question (MCQ) format benchmarks requires further validation, though GSM8K (open-ended) shows consistent patterns.

References

- Terry A Ackerman. 1992. A didactic explanation of item bias, item impact, and item validity from a multidimensional perspective. *Journal of Educational Measurement*, 29(1):67–91.
- Gregory Camilli and Lorrie A. Shepard. 1994. *Methods for Identifying Biased Test Items*. Sage Publications, Thousand Oaks, CA.
- Nicholas Carlini, Daphne Ippolito, Matthew Jagielski, Katherine Lee, Florian Tramèr, and Chiyuan Zhang. 2023. [Quantifying memorization across neural language models](#). In *International Conference on Learning Representations (ICLR)*.
- Yupeng Chang, Xu Wang, Jindong Wang, Yuan Wu, Kaijie Zhu, Hao Chen, Linyi Yang, Xiaoyuan Yi, Cunxiang Wang, Yidong Wang, Wei Ye, Yue Zhang, Yi Chang, Philip S. Yu, Qiang Yang, and Xing Xie. 2024. [A survey on evaluation of large language models](#). *ACM Transactions on Intelligent Systems and Technology*.
- Brian E. Clauser and Kathleen M. Mazor. 1998. [Using statistical procedures to identify differentially functioning test items](#). *Educational Measurement: Issues and Practice*.
- Jasper Dekoninck, Mark Niklas Mueller, and Martin Vechev. 2024. [ConStat: Performance-based contamination detection in large language models](#). In *Advances in Neural Information Processing Systems (NeurIPS)*.
- John R. Donoghue and Nancy L. Allen. 1993. An empirical examination of the Mantel-Haenszel statistic for the study of differential item functioning. *Applied Measurement in Education*, 6(2):163–179.
- Brian F. French and W. Holmes Finch. 2010. Hierarchical logistic regression: Accounting for multilevel data in DIF detection. *Journal of Educational Measurement*, 47(3):299–317.
- Aryo Pradipta Gema, Joshua Ong Jun Leang, Giwon Hong, Alessio Devoto, Alberto Carlo Maria Mancino, Rohit Saxena, Xuanli He, Yu Zhao, Xiaotang Du, Mohammad Reza Ghasemi Madani, Claire Barale, Robert McHardy, Joshua Harris, Jean Kadour, Emile van Krieken, and Pasquale Minervini. 2024. [Are we done with MMLU?](#) *Preprint*, arXiv:2406.04127.
- Eliya Habba, Itay Itzhak, Asaf Yehudai, Yotam Perlitz, Elron Bandel, Michal Shmueli-Scheuer, Leshem Choshen, and Gabriel Stanovsky. 2026. [Growing pains: Extensible and efficient LLM benchmarking via fixed parameter calibration](#). *Preprint*, arXiv:2604.12843.
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. [Measuring massive multitask language understanding](#). In *Proceedings of the International Conference on Learning Representations (ICLR)*.

675	Paul W. Holland and Dorothy T. Thayer. 1988. Dif-	729
676	ferential item functioning and the Mantel-Haenszel	730
677	procedure. In Howard Wainer and Henry I. Braun,	731
678	editors, <i>Test Validity</i> . Lawrence Erlbaum Associates.	
679	Douwe Kiela, Max Bartolo, Yixin Nie, Divyansh	732
680	Kaushik, Atticus Geiger, Zhengxuan Wu, Bertie Vid-	733
681	gen, Grusha Prasad, Amanpreet Singh, Pratik Ring-	734
682	shia, Zhiyi Ma, Tristan Thrush, Sebastian Riedel,	
683	Zeeraq Talat, Pontus Stenetorp, and Robin Jia. 2021.	735
684	Dynabench: Rethinking benchmarking in NLP . In	736
685	<i>Proceedings of the 2021 Conference of the North</i>	737
686	<i>American Chapter of the Association for Computa-</i>	738
687	<i>tional Linguistics (NAACL)</i> .	
688	Alon Kipnis, Konstantinos Voudouris, Luca Maria	
689	Schulze Buschoff, and Eric Schulz. 2024. metabench	
690	– a sparse benchmark of reasoning and knowledge in	
691	large language models . <i>Preprint</i> , arXiv:2407.12844.	
692	Leslie Kish. 1965. <i>Survey Sampling</i> . John Wiley &	
693	Sons, New York.	
694	John Lalor, Hao Wu, and Hong Yu. 2019. Learning	
695	latent parameters without human response patterns:	
696	Item response theory with artificial crowds . In <i>Pro-</i>	
697	<i>ceedings of the 2019 Conference on Empirical Meth-</i>	
698	<i>ods in Natural Language Processing and the 9th In-</i>	
699	<i>ternational Joint Conference on Natural Language</i>	
700	<i>Processing (EMNLP-IJCNLP)</i> .	
701	Yucheng Li, Yunhao Guo, Frank Guerin, and Chenghua	
702	Lin. 2024. An open-source data contamination re-	
703	port for large language models . In <i>Findings of the</i>	
704	<i>Association for Computational Linguistics: EMNLP</i>	
705	<i>2024</i> .	
706	Rongzhen Liang. 2026. DVD: A robust method for	
707	detecting variant contamination in large language	
708	model evaluation . <i>Preprint</i> , arXiv:2601.04895.	
709	David Magis, Sébastien Béland, Francis Tuerlinckx, and	
710	Paul De Boeck. 2010. A general framework and an	
711	R package for the detection of dichotomous differen-	
712	tial item functioning . <i>Behavior Research Methods</i> ,	
713	42(3):847–862.	
714	William Meredith. 1993. Measurement invariance, fac-	
715	tor analysis and factorial invariance . <i>Psychometrika</i> .	
716	Randall D. Penfield and Gregory Camilli. 2007. Differ-	
717	ential item functioning and item bias . In <i>Handbook</i>	
718	<i>of Statistics</i> , volume 26, pages 125–167. Elsevier.	
719	J. N. K. Rao and A. J. Scott. 1992. A simple method	
720	for the analysis of clustered binary data. <i>Biometrics</i> ,	
721	48(2):577–585.	
722	Louis A Roussos and William F Stout. 1996. A new	
723	view of the effect of multidimensionality on the	
724	Mantel-Haenszel and SIBTEST procedures. <i>Jour-</i>	
725	<i>nal of Educational Measurement</i> , 33(3):278–295.	
726	Weijia Shi, Anirudh Ajith, Mengzhou Xia, Yangsibo	
727	Huang, Daogao Liu, Terra Blevins, Danqi Chen, and	
728	Luke Zettlemoyer. 2024. Detecting pretraining data	
	from large language models . In <i>Proceedings of the</i>	
	<i>International Conference on Learning Representa-</i>	
	<i>tions (ICLR)</i> .	
	Youmi Suk and Weijun Lyu. 2026. Rethinking dif-	
	ferential item functioning from a causal inference	
	perspective. <i>Psychometrika</i> . Forthcoming.	
	Hariharan Swaminathan and H. Jane Rogers. 1990. De-	
	tecting differential item functioning using logistic	
	regression procedures . <i>Journal of Educational Mea-</i>	
	<i>surement</i> .	
	Yongding Tao, Tian Wang, Yihong Dong, Huanyu Liu,	
	Kechi Zhang, Xiaolong Hu, and Ge Li. 2026. Detect-	
	ing data contamination from reinforcement learning	
	post-training for large language models . In <i>Proce-</i>	
	<i>edings of the International Conference on Learning</i>	
	<i>Representations (ICLR)</i> .	
	Howard Wainer and Henry I. Braun. 1993. <i>Differential</i>	
	<i>Item Functioning</i> . Lawrence Erlbaum Associates,	
	Hillsdale, NJ.	
	Haonan Wang, Haoyang Li, Boeun Ko, and Hongyang	
	Zhang. 2026. On the fragility of benchmark conta-	
	mination detection in reasoning models . In <i>Proceed-</i>	
	<i>ings of the International Conference on Learning Rep-</i>	
	<i>resentations (ICLR)</i> .	
	Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali	
	Farzaneh, and Yejin Choi. 2019. HellaSwag: Can a	
	machine really finish your sentence? In <i>Proceedings</i>	
	<i>of the 57th Annual Meeting of the Association for</i>	
	<i>Computational Linguistics (ACL)</i> , pages 4791–4800.	
	Qihao Zhao, Yangyu Huang, Tengchao Jing, Xiaom-	
	ing Shi, Yanan Liang, Jiaqing Du, Wenbo He, and	
	Yankai Lin. 2025. MMLU-CF: A contamination-	
	free multi-task language understanding benchmark .	
	In <i>Proceedings of the 63rd Annual Meeting of the</i>	
	<i>Association for Computational Linguistics (ACL)</i> .	
	Hongli Zhou, Hui Huang, Ziqing Zhao, Lvyuan Han,	
	Huicheng Wang, Kehai Chen, Muyun Yang, Wei	
	Bao, Jian Dong, Bing Xu, Conghui Zhu, Hailong	
	Cao, and Tiejun Zhao. 2026. Lost in benchmarks?	
	rethinking large language model benchmarking with	
	item response theory . In <i>Proceedings of the AAAI</i>	
	<i>Conference on Artificial Intelligence (AAAI)</i> .	
	Longyuan Zhu, Hairan Hua, Linlin Miao, and Bing	
	Zhao. 2026. Benchmark health index: A system-	
	atic framework for benchmarking the benchmarks of	
	LLMs . <i>Preprint</i> , arXiv:2602.11674.	
	A Method Details	
	A.1 Diagnostics	
	Three diagnostic procedures complement the pri-	
	mary DIF analysis.	

Local independence (Yen’s Q3). The MH procedure assumes that item responses are conditionally independent given θ . Yen’s Q3 statistic measures residual correlations between item pairs after conditioning on the latent trait. We compute Q3 for all within-subject and cross-subject item pairs, with $|Q3| > 0.20$ as the threshold for local dependence. Elevated within-subject dependence would indicate that items within the same subject share variance beyond what θ captures, which could inflate within-subject DIF rates.

Domain-specificity. We test whether temporal DIF concentrates in domains where models improved most. At the ecological level, we compute Spearman ρ between subject-level C% and subject-level accuracy improvement from 2023 to 2024. At the item level, logistic regression predicts item-level DIF C classification from domain-level accuracy change, with and without item property controls (difficulty, discrimination). This decomposition quantifies how much of the observed instability is attributable to aggregate domain-level gains versus item-specific behavioral change.

Instability decomposition. When domain accuracy improvement is included alongside item-level controls, we compute the counterfactual C% that would remain after removing domain-level effects. The gap between observed and counterfactual C% measures the contribution of domain-level improvement to the total instability.

A.2 Statistical Considerations

Multiple testing. The ETS C classification imposes a dual threshold (effect size $|\Delta_{MH}| \geq 1.5$ and significance $p < 0.05$), which provides implicit control over false positives. As a robustness check, we apply Benjamini-Hochberg FDR correction at $q = 0.05$. The random-split sanity check provides an empirical estimate of the false positive rate under the null hypothesis.

Threshold sensitivity. We report results across a range of DIF thresholds ($|\Delta_{MH}| \in \{1.0, 1.5, 2.0, 2.5\}$) to verify that qualitative conclusions do not depend on the specific ETS C cutoff. The standard threshold of $|\Delta_{MH}| \geq 1.5$ corresponds to the ETS C definition used throughout the paper.

IRT model fit. For transparency, we report that the MMLU response matrix shows poor fit to a unidimensional 2PL model (expected for a 57-subject

multidimensional benchmark). This does not affect MH-DIF validity, which relies only on total score stratification rather than parametric IRT assumptions.

Architecture heterogeneity. The METABENCH MMLU population consists of 99.98% decoder-only models (5,226 of 5,227). This near-complete architectural homogeneity eliminates architecture as a confound for DIF analysis. We verify this by excluding the single encoder-decoder model and confirming identical results.

Power sensitivity to item discrimination. The Monte Carlo power analysis in Section 4.1 uses average 2PL parameters ($\bar{a} = 1.2$, $\bar{b} = -0.84$). Table 3 reports TPR as a function of discrimination a (other parameters at their means, $N = 80$ per cohort, $|\Delta_b| = 1.4$, 1,000 replications). TPR increases monotonically from 0.40 ($a = 0.5$) to 0.95 ($a = 2.0$); FPR remains below 0.04 throughout. The MMLU item pool shows substantial heterogeneity: a ranges from 0.006 to 2.657 (SD = 0.54, IQR = [0.75, 1.64]). The aggregate TPR of 0.68 from Phase 2 reflects this full distribution, while TPR at mean $a \approx 1.2$ is 0.87—the gap is consistent with Jensen’s inequality applied to the concave TPR(a) function. Although 2PL fit is poor for MMLU’s multidimensional structure, the power analysis serves as one leg of a triangulation: parametric estimates (TPR = 0.68–0.80) are validated by empirical semi-synthetic injection ($\Delta\text{TPR} = +0.508$ at $p = 0.5$; Section 4.5), confirming adequate detection power regardless of parametric assumptions.

Table 3: Power sensitivity to item discrimination. TPR = true positive rate for ETS C detection ($|\Delta_{MH}| \geq 1.5$) at $N = 80$ per cohort, $|\Delta_b| = 1.4$, 1,000 replications.

a	TPR	95% CI	FPR
0.5	0.398	[0.20, 0.60]	0.033
0.8	0.683	[0.45, 0.90]	0.036
1.0	0.808	[0.60, 0.95]	0.038
1.2 ($\approx \bar{a}$)	0.874	[0.70, 1.00]	0.038
1.5	0.930	[0.80, 1.00]	0.038
2.0	0.949	[0.80, 1.00]	0.037

Stratum sensitivity (K=3 vs. K=5). K=3 and K=5 yield near-identical detection power: TPR differences < 0.02 across all conditions, within Monte Carlo noise. TPR ranges from 0.454 ($N=80$) to 0.571 ($N=100$) at $|\Delta_{MH}| \geq 1.4$, with AUC of

0.905 at $N=100$, confirming that smaller corpora can use fewer strata without power loss (Table 4).

Table 4: Detection power: K=3 vs. K=5 at $|\Delta_{MH}| \geq 1.0$.

N/cohort	K=3			K=5		
	TPR	FPR	AUC	TPR	FPR	AUC
80	0.176	0.001	0.828	0.169	0.001	0.826
200	0.623	0.004	0.939	0.621	0.004	0.934
500	0.915	0.011	0.986	0.912	0.013	0.986

Nearest-neighbor matching. The 1:1 nearest-neighbor matching selects, for each focal-cohort model, the reference-cohort model with the closest total score (caliper of 0.02 on normalized accuracy, approximately 0.14 SD). Balance is verified by Cohen’s $d = -0.17$ on matched pairs ($N = 638$ per group), confirming minimal residual ability confounding.

Logistic regression specification. The Simpson’s paradox analysis (Section 4.2) uses binary logistic regression with DIF-C classification as the dependent variable, domain-level accuracy change (2024 minus 2023 mean accuracy) as the primary predictor, and item difficulty (proportion correct) and IRT discrimination (point-biserial correlation) as controls. The interaction between domain accuracy change and item difficulty is included. Non-uniform DIF detection (Section 4.4) uses logistic regression with a group $\times$ ability interaction term; a significant interaction ($p < 0.05$) indicates non-uniform DIF.

B Mechanism Analysis

Three non-exclusive mechanisms may drive the observed 13.5–29.2% temporal DIF rate (after non-independence corrections): (1) differential contamination, where newer models encounter benchmark items during training; (2) capability evolution, where training advances shift item–ability relationships; (3) training methodology shifts (e.g., RLHF, instruction tuning). The ETS baseline of 5–15% C% (Clauser and Mazor, 1998) applies to concurrent demographic groups in educational testing; comparison to temporal LLM cohorts is illustrative, not normative. Observational DIF alone cannot separate these mechanisms (Suk and Lyu, 2026); the evidence below constrains the space of explanations.

Exclusion arguments. Four exclusion arguments narrow possible explanations. *Ability confounds:* at most 2.4 pp attributable to ability mismatch (matched C% = 28.9% vs. unmatched 31.3%; Cohen’s $d = -0.17$; Section 4.2). *Domain-level improvement:* domain accuracy gains explain $<0.1\%$ of item-level DIF variance (pseudo $R^2 = 0.0007$); a Simpson’s paradox confirms DIF is item-specific (OR reverses from 1.55 to 0.73 after difficulty control). *Item quality defects:* no enrichment among expert-annotated errors (Gema et al., 2024) (enrichment = 1.10, 95% CI [0.92, 1.27], $p = 0.23$). *Web-overlap labels:* near-independent of DIF flags (Jaccard = 0.206, enrichment = 0.964; Section 4.3).

Difficulty–direction interaction. The aggregate difficulty–direction correlation ($r = -0.597$; Section 4.2) shows that hardest-decile DIF-C items are 88.7% focal-favoring while easiest-decile items are 96.2% reference-favoring. This gradient is robust under range restriction ($r = -0.447$ at difficulty $\in [0.2, 0.8]$; $p < 10^{-100}$). Semi-synthetic analysis (Section 4.5) reveals that uniform injection produces $r \approx -0.52$ via ceiling effects (high-accuracy items have fewer flippable responses), while difficulty-dependent injection yields $r \approx +0.77$ (zero overlap across seeds). The observed r thus cannot alone distinguish contamination from capability evolution.

Difficulty–model-type interaction. Logistic regression confirms that the base-vs-instruct direction reversal is not a difficulty confound: the difficulty $\times$ model-type interaction is significant ($\hat{\beta} = 1.56$, OR = 4.75, $p < 10^{-188}$; $N = 8,585$ items). Controlling for difficulty, model type remains a strong independent predictor of DIF direction (OR = 4.24, $p < 10^{-225}$). Among 2,053 items flagged DIF-C in both base and instruct analyses, 98% show concordant direction; the aggregate reversal arises from *which* items reach C threshold, not from individual items reversing direction.

Mixed-mechanism injection. To test the hypothesis that different contamination mechanisms operate on base and instruct models simultaneously, we designed mixed injection schemes: Scheme D applies difficulty-dependent injection to base models and uniform injection to instruct models. Across 20 seeds, Scheme D reproduces the overall difficulty–direction gradient ($r = -0.676 \pm 0.005$ vs. observed -0.597) and direction reversal ($\chi^2 = 634 \pm 184$ vs. observed 562.7), but cannot match the

near-zero instruct gradient: simulated $r_{\text{instruct}} = -0.302 \pm 0.090$ vs. observed -0.079 . This residual gap ($3.8\times$ the observed value) persists across all tested injection parameters, suggesting that instruct-model DIF is at least partially driven by non-contamination mechanisms (e.g., alignment-induced capability shifts) rather than memorization alone.

C Structural Analysis Details

Table 5: Structural controls and sensitivity checks for temporal DIF. None reduces C% below 31%; θ -conditioning serves as a sensitivity check confirming total-score adequacy.

Approach	Mechanism	Temp. C%	TPR ($p=0.5$)	Outcome
Baseline (ext.)	Cross-bench. total score	$0.314 \pm .009$	$0.834 \pm .027$	Reference
Matched-ability	Within-quintile temp. DIF	~ 0.31	—	Enrich. 0.94–1.04
θ -cond. (sens.)	θ replaces total score	0.312	0.876	$r(\theta, \text{total}) = 0.9986$
Within-subject	Per-subject DIF	—	—	C% = 38.1% ($>25\%$)

Two structural controls and a sensitivity check fail to reduce the temporal C% below 31%, revealing a structural property of the data rather than a methodological limitation. Matched-ability quintile analysis restricts comparisons to models of similar total score and yields enrichment ratios of 0.94–1.04, with temporal C% unchanged at approximately 0.31. Within-subject DIF analysis on 5 representative subjects, intended to isolate subject-specific effects, finds mean C% = 38.1%, exceeding the 25% threshold that would indicate viable bifactor structure. As a sensitivity check, IRT θ -conditioning with 20 ability strata achieves $r(\theta, \text{total score}) = 0.9986$ and C% = 0.312, confirming that the external total score already captures nearly all ability variance relevant to DIF computation. Table 5 summarizes these results.

The temporal FPR reflects genuine item-level instability that persists regardless of how ability is measured or conditioned. Yen’s Q3 diagnostic reveals mild local dependence within subjects (11.3% of within-subject item pairs exceed $|Q3| > 0.20$, vs. 2.2% cross-subject; $5\times$ ratio, $p = 2.3 \times 10^{-9}$), which contributes to elevated within-subject DIF rates but is not the primary driver: the cross-subject matching protocol addresses this bias, and temporal C% persists under external matching (full Q3 distributions available in the supplementary material).

Extreme contamination coverage ($k \geq 30$). At $k = 30$ – 50 (53–88% of 57 subjects), ΔFPR reaches 0.36–0.46, confirming that cross-subject

Table 6: Domain-level Cohen’s d between 2023 and 2024 cohorts. The narrow range (0.12) indicates nearly uniform improvement across domains, supporting total-score matching adequacy for DIF analysis (Section 3).

Domain	Cohen’s d
STEM	0.261
Humanities	0.159
Social Science	0.147
Other	0.146

Table 7: Multi-subject injection robustness. k = number of simultaneously contaminated subjects (out of 57); values are mean $\pm$ SD across 5 random subject draws at exploitation rate $p = 0.5$. Cross-subject matching provides reliable FPR control at $k \leq 5$; ΔFPR increases substantially at $k \geq 10$.

k	ΔFPR	ΔTPR
1	$0.002 \pm .002$	$0.518 \pm .050$
3	$0.000 \pm .003$	$0.470 \pm .093$
5	$0.007 \pm .007$	$0.421 \pm .041$
10	$0.069 \pm .030$	$0.361 \pm .027$
20	$0.167 \pm .029$	$0.299 \pm .030$
30	$0.362 \pm .026$	$0.159 \pm .035$
50	$0.458 \pm .053$	$0.439 \pm .028$

matching requires contamination to affect a minority of domains. At extreme coverage the matching variable itself is majority-contaminated, violating the identifying assumption. ΔTPR drops to 0.159 at $k=30$ as matching-variable corruption dominates; at $k=50$, both ΔTPR (0.439) and ΔFPR (0.458) surge to comparable levels, indicating the test flags $\sim 76\%$ of all items regardless of contamination status—complete loss of discriminative power. This regime is primarily of theoretical interest: if $\geq 50\%$ of benchmark domains are differentially contaminated, the benchmark requires redesign rather than statistical correction.

D Design Effect Estimation

Model families (e.g., Mistral, Llama-3) induce intra-class correlation (ICC) that inflates Mantel-Haenszel χ^2 statistics beyond the nominal χ^2_1 reference distribution. We estimate the design effect (DEFF) per item following Rao and Scott (1992): $\text{DEFF}_i = 1 + (\bar{m} - 1) \cdot \text{ICC}_i$, where $\bar{m}$ is the mean family size and ICC_i is the one-way random-effects ICC for item i across 30 families (restricted to ref+foc cohort; 1,884 models with family ≥ 2).

Two estimates of $\bar{m}$ bracket the adjustment: (1) *Simple mean* ($\bar{m} = 62.8$), treating all families equally, yields $\text{DEFF} = 3.87$ and adjusted C% =

Table 8: Leave-one-family-out (LOFO) robustness on MMLU. Removing non-dominant families ($\leq 15\%$ of their cohort) changes C% by at most 2.93 pp. Larger shifts from removing Mistral or Llama-3 are driven almost entirely by family composition, not statistical power loss: Monte Carlo random-subsample calibration (200 replicates per scenario, matching the reduced sample size) shows the power effect is ≤ 1 pp, while the composition effect accounts for 95–113% of the observed C% drop (Mistral: -8.44 pp composition vs. -0.41 pp power; Llama-3: -8.17 pp vs. $+0.91$ pp; observed C% falls below the 95% random-subsample range in both cases). Stratification uses total test score for computational efficiency; cross-subject matching yields identical baseline C%.

Family	N removed	Cohort share	C% (LOFO)
<i>Full sample</i>	—	—	31.32
Mistral	547	51% ref	22.47
Llama-3	315	39% foc	24.06
Mixtral	120	15% foc	34.26
Llama-2	161	15% ref	31.48
Solar	91	11% foc	31.01

29.2%; (2) *Weighted mean* ($\bar{m} = \sum n_f^2 / \sum n_f = 254.5$; Kish, 1965), reflecting the effective cluster size experienced by a randomly sampled model, yields DEFF = 12.79 and adjusted C% = 13.5%. Mean ICC = 0.047 (median 0.041, Q3 = 0.061, max = 0.219; 4.8% of items exceed 0.10). After dividing each item’s χ_{MH}^2 by its item-specific DEFF and re-applying ETS thresholds, 13.5–29.2% of items retain Category C classification depending on the $\bar{m}$ variant—both far exceeding the 0.62% random-split baseline ($21\text{--}47\times$).

Size-stratified DEFF. The aggregate ICC masks a size–ICC inverse relationship: smaller families exhibit higher within-family similarity (Table 9). Tier-level ICC ranges from 0.246 (2–10 members) to 0.082 (>200 members), reflecting greater heterogeneity in mega-families. At small family sizes, DEFF correction has negligible impact (Adj. C% = 31.3%); the conservative 13.5% bound is driven entirely by the two mega-families (Mistral, Llama-3). Family definition sensitivity is minimal: merging sub-generations (e.g., Llama-2 + Llama-3) into coarse families (22 families) changes C% by ≤ 0.3 pp.

E Uncertainty Quantification Comparison

Half-year granularity. Splitting at the 6-month boundary yields C% = 34.4%, slightly above the

Table 9: Size-stratified DEFF analysis. ICC and DEFF computed per tier; Adj. C% applies tier-specific DEFF to all items.

Tier	Families	$\bar{m}$	ICC	DEFF	Adj. C%
2–10	9	5.3	0.246	2.07	31.3%
11–50	11	22.1	0.226	5.78	24.6%
51–200	8	91.4	0.137	13.34	13.7%
>200	2	431.0	0.082	36.11	9.0%
Overall	30	62.8	0.047	3.87	29.2%

Table 10: Comparison of uncertainty quantification methods for the 31.3% C% estimate on MMLU.

Method	Key assumption	Result
Model-level bootstrap	Models independent	95% CI [29.2%, 37.8%]
Family-level cluster bootstrap	Family is clustering unit	95% CI [26.7%, 53.2%]
DEFF (simple $\bar{m}$)	Equal-weight families	Adjusted C% = 29.2%
DEFF (weighted $\bar{m}$)	Size-proportional weighting	Adjusted C% = 13.5%
Graduated de-dup. ($K=20$)	Remove within-family duplicates	C% = $19.7\% \pm 0.9\%$

annual 31.3%. The higher rate likely reflects more polarized cohort composition: fewer models span both half-year periods, producing reference and focal groups with less overlapping ability distributions and consequently inflated DIF detection rates.

The cluster bootstrap upper bound (53.2%) is driven by extreme bootstrap resamples that over-represent Mistral ($n = 547$) or Llama-3 ($n = 315$), producing atypical cohort compositions. Two independent methods—cluster bootstrap lower bound (26.7%) and simple-mean DEFF adjustment (29.2%)—converge on $\sim 27\text{--}29\%$, establishing a corrected estimate that remains $>45\times$ the random-split baseline (0.62%). Graduated de-duplication at $K=20$ yields C% = $19.7\% \pm 0.9\%$ (random member selection, 5 draws), lower than the corrected estimate due to reduced statistical power ($N \approx 450$ vs. 1,887), but within- K variance <1.5 pp at all K confirms the signal is power-driven rather than redundancy-inflated (Section J). The weighted-mean DEFF (13.5%) represents a conservative extreme; even this lower bound exceeds the baseline by $\approx 22\times$.

F Cross-Benchmark Comparison

G Additional Figures

See Figure 4 in the main text for ranking degradation curves.

H Item-Property Predictive Analysis

To test whether DIF susceptibility is a fixed item property, we trained logistic regression and Light-

Table 11: Cross-benchmark comparison of DIF analysis on MMLU and GSM8K. Both benchmarks exhibit temporal score incomparability with validated semi-synthetic detection power. Standard and external matching use different exploitation rates (p) because each benchmark’s optimal operating point differs; external matching results are compared at $p = 0.5$ for both. Subscript $\pm$ values denote standard deviations across 5 random injection seeds.

Metric	MMLU	GSM8K
Items	12,508	1,319
Models	5,227	6,702
Temporal C%	31.3%	18.9%
Sanity C%	0.62%	0.3%
ΔTPR ($p=0.7$, standard)	—	$+0.818 \pm .006$
ΔTPR ($p=0.5$, external)	$+0.508 \pm .027$	$+0.514 \pm .028$

GBM classifiers to predict ETS C classification from 17 leak-free features: ref-cohort difficulty and discrimination, 11 text features (question/option length, vocabulary metrics), subject metadata, and web-overlap labels (Li et al., 2024). Features were computed exclusively from the reference (2023) cohort to prevent information leakage from the focal cohort. Five-fold subject-stratified cross-validation (no within-subject train/test overlap) yielded AUROC = 0.603 ± 0.020 (LR) and 0.599 ± 0.026 (LightGBM)—weak predictive power. Web-overlap labels contributed negligibly (SHAP < 0.015), independently confirming the DIF–contamination orthogonality reported in Section 4.3. These results indicate that temporal DIF reflects emergent cohort–item interactions rather than fixed item defects, motivating post-hoc monitoring over pre-screening.

I Within-Family Similarity by Family Size

Within-family similarity (mean pairwise Pearson r over 12,508-item response vectors) shows no dependence on family size (Spearman $\rho = -0.009$, $p = 0.96$; 30 families with ≥ 2 members, 1,884 models). Large families (Mistral, $m = 547$, $\bar{r} = 0.47$; Llama-3, $m = 315$, $\bar{r} = 0.53$) are no more homogeneous than small or mid-sized families. Of the 5,227 models, 3,343 lack family assignments; these are retained in DIF analysis but excluded from similarity estimation. Within the temporal DIF cohorts ($N_{\text{ref}} + N_{\text{foc}} = 1,887$), 1,884 (99.8%) belong to identified families with ≥ 2 members, so DEFF estimates are computed over nearly the full cohort. This indicates that the




Figure 7: Exploratory: GSM1K contamination gap vs. DIF ranking advantage ($N = 33$; small sample, results should be interpreted cautiously). The negative correlation ($r = -0.478$, $p = 0.005$) indicates that models with larger contamination gaps benefit less from DIF-flagged items. Three of 33 models exceed the Cook’s D threshold ($4/N = 0.12$); leave-one-out analysis confirms all individual-removal correlations remain significant ($r \in [-0.54, -0.37]$, all $p < 0.05$), and removing all three outliers yields $r = -0.38$ ($p = 0.036$, $N = 30$).

weighted-mean DEFF variant’s effective cluster size ($\bar{m} = 254$) reflects an arithmetic artifact of mega-family dominance rather than genuine within-family homogeneity.

J Graduated De-Duplication Sensitivity

For each value of K (max models retained per family), K members are sampled uniformly at random; remaining family members are excluded from both reference and focal cohorts, and MH-DIF is recomputed on the reduced sample (5 independent draws per K ; $K = \text{all}$ is deterministic).

C% increases monotonically from 0.3% ($K = 1$) to 31.3% ($K = \text{all}$). At each fixed K , variance across random member draws is negligible (SD < 1.5 pp), confirming that the signal scales with statistical power rather than within-family redundancy. At $K=20$, C% = $19.7\% \pm 0.9\%$ ($N \approx 450$); the gap from the full-sample 31.3% reflects reduced power, not reduced bias.

K Rank-Reversal by Distance

Pairwise rank reversals between full-item and stable-item rankings concentrate among closely-ranked models. At $\Delta\text{rank} < 50$ (mean $\Delta\text{acc} = 0.003$, effectively statistical ties), the reversal rate is 35.2%. It drops to 15.1% for $\Delta\text{rank} \in [50, 200)$, 4.0% for $[200, 500)$, 0.6% for $[500, 1000)$, and

0.0% above 1000. Broad leaderboard structure is fully preserved; instability affects only models within each other’s noise margin.

L DEFF Simulation

To compare simple-mean and weighted-mean DEFF estimators, we simulate four family-structure scenarios (2,000 items, 30% ground-truth DIF, 50 seeds per scenario) with size-dependent ICC matching empirical observations (Table 9). Table 12 reports the results.

Table 12: DEFF estimator comparison across four simulated family structures. Bias = adjusted C% – ground truth (30%); RMSE over 50 seeds. Simple-mean wins in 3/4 scenarios; weighted-mean ties only under uniform family sizes.

Scenario	$\bar{m}_s$	$\bar{m}_w$	Adj(s)	Adj(w)	RMSE(s)	RMSE(w)
A: Uniform	35	35	2.1%	2.1%	27.9	27.9
B: Skewed	40	168	2.3%	0.9%	27.7	29.1
C: Extreme	33	268	2.4%	0.5%	27.6	29.5
D: Homog. ICC	40	168	4.1%	1.1%	25.9	28.9

When ICC decreases with family size (scenarios B–D, matching empirical patterns), larger families contribute less per-model inflation than the weighted-mean assumes. The weighted-mean over-corrects by assigning excessive weight to mega-families whose low ICC does not warrant large DEFF adjustments. The simple-mean estimator better captures the average inflation per family under these conditions.

M Score Inflation Analysis

Removing the 3,918 DIF-C items (31.3%) and rescoring on the 8,590 stable items shifts model accuracy upward by a mean of +2.12 pp overall (Table 13). The cohort-differential is 0.29 pp (2023: +2.35 pp; 2024: +2.06 pp; Cohen’s $d = 0.31$, $p < 10^{-10}$). Overall ranking correlation between original and stable-item scores is $\rho = 0.9965$, but individual rank displacements reach ± 561 at the 99th percentile and exceed ± 800 in extreme cases. Equating adjustments are +0.0235 (2023) and +0.0206 (2024).

Table 13: Score inflation from DIF-C item removal, by cohort.

Cohort	N	Mean Δ (pp)	SD (pp)	95% CI
2023	1,080	+2.35	0.88	[+2.30, +2.40]
2024	807	+2.06	1.04	[+1.99, +2.13]
Other	3,340	+2.05	0.92	[+2.02, +2.08]

N Within-Architecture Temporal DIF

To rule out the confound that overall temporal DIF is driven by cross-architecture differences, we group fine-grained families into architecture lineages and run MH-DIF within each (Table 14).

Table 14: Within-architecture temporal DIF. C% = ETS C items between 2023 and 2024 models within each lineage.

Lineage	N_{ref} (2023)	N_{foc} (2024)	C%	Med $ \Delta $
Llama	171	315	59.2%	2.38
Qwen	27	70	6.9%	1.55
Yi	72	14	3.5%	1.78
Phi	60	20	1.3%	2.85

Llama, Qwen, and Yi show C% above the random baseline; Phi (C% = 1.3%, $N_{\text{foc}} = 20$) is inconclusive due to low power. Llama is the best-powered comparison ($N = 486$ total) and yields raw C% = 59.2%, which combines temporal and generational effects. After ability matching, within-architecture C% converges to ~ 28 –29%, consistent with temporal C% (28.9%)—confirming that the temporal DIF signal persists within individual lineages and is not an artifact of comparing different architectures.

O Base-Only and Instruct-Only Temporal DIF

Separating the temporal cohorts by model type confirms that both base and instruct models independently exhibit substantial temporal DIF (Table 15). Training methodology modulates DIF *direction* (base: 60.1% reference-favoring with $r = -0.570$; instruct: 65.6% focal-favoring with $r = -0.079$) rather than DIF *magnitude*, providing direct evidence against composition shift as the primary driver.

Table 15: Temporal DIF computed separately for base-only and instruct-only model subsets. Both model types independently exhibit C% $\geq 32\%$, far exceeding the random baseline (0.62%). Training methodology modulates DIF direction (r , focal-favoring proportion) rather than magnitude.

Subset	$N_{\text{ref}} / N_{\text{foc}}$	C%	$\rho(\text{diff}, \Delta_{\text{MH}})$	Focal-fav
Base-only	861 / 548	32.1%	−0.570	39.9%
Instruct-only	219 / 259	36.5%	−0.079	65.6%
Overall	1,080 / 807	31.3%	−0.587	43.9%

P Composition Control

The 2023 and 2024 cohorts differ in base/instruct composition (2023: 79.7% base; 2024: 67.9% base; 11.8 pp gap). To test whether this confounds temporal DIF, we downsample 2023 base models to match the 2024 ratio and re-run MH-DIF (10 random seeds). Balanced C% = $30.25\% \pm 1.32\%$ (95% CI: [27.65%, 32.84%]), differing from the original 31.3% by only 1.08 pp. Composition shift does not explain the observed temporal DIF rate.

Q Use of AI Assistants

We used Claude (Anthropic) as an AI coding and writing assistant throughout this work. Specifically:

- **Code:** drafting experiment scripts, data-processing pipelines, and analysis utilities; debugging and refactoring.
- **Writing:** drafting and revising paper sections, polishing prose, and reformatting $\text{\LaTeX}$.
- **Literature:** summarizing related papers to inform the related-work section.