


Dual Technology Features Automatic Selection of Magnetic Induction or Eddy Current Measurement Techniques



Model 156



EMC
EN: 61326



Features

	150	156	156H
Non-magnetic coatings(e.g. paint, zinc)on steel	*	*	*
Insulating coatings(e.g. paint)on no-ferrous metals	*	*	*
No-ferrous metals coatings on insulating substrates	*	*	*
Menu operation system		*	*
Two measuring modes: CONTINUE and SINGLE mode		*	*
Two working modes: DIRECT and GROUP mode		*	*
Statistic Display: AVG, MAX, MIN, NO., S.DEV		*	*
One point calibration, two points calibration and basic calibration easily		*	*
Memory for 400 readings(80 DIRECT and 320 GROUP readings)		*	*
Memory for 1500 readings(30 GROUP readings)			*
Delete single readings and all group readings easily		*	*
High alarm and Low alarm for all working modes		*	*
Low battery, error indication		*	*
USB interface for PC software		*	*
4 levels of battery indication			*
Error indication			*
Easily adapt to lighting conditions with 8 levels of backlight			*



Model 156H



EMC
EN: 61326

Specifications

	150	156		156H	
Sensor probe		F	N	F	N
Working principle		Magnetic induction	Eddy current principle	magnetic induction	Eddy current principle
Measuring range	0.0~2.0 mm/ 0~80 mil	0~1250um	0~1250um	0~1350um	0~1350um
Guaranteed tolerance (of reading)	$\pm (2\%+0.1)\text{mm}/$ $\pm (2\%+4)\text{mil}$	$\pm (3\%+1)\mu\text{m}$	$\pm (3\%+1.5)\mu\text{m}$	$\pm (2.5\%+2)\mu\text{m}$	$\pm (2.5\%+2)\mu\text{m}$
Repeatability		$\pm (1\%+1)\mu\text{m}$	$\pm (1\%+1)\mu\text{m}$	$\pm (1\%+1)\mu\text{m}$	$\pm (1\%+1)\mu\text{m}$
Low range Precision		0.1um	0.1um	0.1um	0.1um
Minimum curvature radius		1.5mm	3mm	1.5mm	3mm
Diameter of Minimum area		7mm	5mm	7mm	5mm
Basic critical thickness		0.5mm	0.3mm	0.5mm	0.3mm



Precision Standard



Calibration Iron



Calibration Aluminum



Model 150

Size(HxWxD): 113.5mm x 54mm x 27mm
Weight: 110g

Accessories:

Two "AAA" batteries, USB cable, CD, Calibration Iron, Calibration Aluminum, Precision Standard, gift box with carrying case.