

Torque Gauges

Torque Gauge Measuring Rotating/Twisting Force

"Torque" is the force that can cause an object to rotate around an axis, fulcrum or pivot. The Unit of torque is N-m/N-cm, Kgf-m/Kgf-cm, or lbf-in/ozf-in.

IMADA torque gauges enable you to measure torque easily and accurately.



Screw Cap Torque Tester

DTXS/DTXA series




Accurately / Precisely

- It captures torque values accurately due to its high sampling rate (2000Hz).
- It is designed to reduce weight influence by its bearing mechanism for greater accuracy.

User friendly

- High Luminance Organic EL display
Clear organic display has excellent readability.
- 8 languages are available
Setting menu in 8 languages helps easy operation.



Making efficient

- High working efficiency due to manual operation
- Easily capture peak value using peak hold function.
- Picks out defective products easily using OK/NG judgement function.

Easy data management on PC

- Easy connection with USB interface
- Data capturing software Force-Logger is included
 - It sends 10 data/sec.
 - It automatically detects maximum and minimum values.
 - It saves data in CSV format.
- Graphing by optional force capturing software
The software shows torque vs time graphically on PC in real time (at Max. 2000Hz). Go to page 12 for further information.



▲ Torque capturing software Force-Logger(Included)



▲ Torque graphing Software Force Recorder (Separately sold)

DTXS

Standard Type

- Size: Approx. W233×D305×H87mm (without the table and the pins.)
- Weight: Approx. 4.5kg (including Standard table and 4 pc Standard pins.)



DTXA

High-functional type

DTXA series include all the functions of DTXS series, with a few additional features below.

Inputting/Outputting Angle

- DTXA indicates both torque and angle on its monitor, combined with an angle meter.
Torque-Angle Analysis with DTXA Go to page 15

Capturing 2 Peaks

- Captures 1st and 2nd peaks of measurement.

Saving Data to USB Flash Drive

- Saves continuous data into USB flash drive at 100Hz.
In other words, data can be saved even without PC.



Check Torque Transition on Graphs

Software Force Recorder ——— To page 12



Transmit Data Wirelessly

Wireless Unit WL01-ADP/WL01-USB ——— To Page 13



Improve Measuring Repeatability

Motorized Torque Test Stand ——— To page 14



Analyze the Relation of Torque and Angle

Torque-Angle Analysis Unit TAA series — To page 15

Accuracy	±0.5%F.S. ±1 digit
Unit of measurement	N-m, N-cm, kgf-m, kgf-cm, lbf-in, ozf-in (switchable)(※1)
Display	4-digit Organic EL
Sampling rate	2000 data / sec at maximum
Function	Customized display (header and footer), Peak hold (clockwise and counter-clockwise), Internal 1000 points data memory, Comparator (judgment of OK or NG), Reversible display, Sign inversion, Zero clear timer, +NG alarm, Off timer (auto power off), Dumping Time display 1st/2nd peak (only for DTXA), Angle detection at torque peak value (only for DTXA)(※2), Angle zero reset at selected torque (only for DTXA)(※2)
Output	USB, RS232C, ±2 VDC analog output (D/A), Comparator 3 steps (-NG/OK/+NG), Overload alarm Sub comparator 2 steps (output of large or small judgment) (only for DTXA), USB flash drive (only for DTXA), Angle (displacement) (only for DTXA) (※2)
Accessory	CD driver (including simple software for data logging), USB cable, AC adapter, Carrying case, Instruction manual, Inspection certificate, L wrench, Handles (10N-m range only), USB flash drive adapter (only for DTXA) (※3)

※1 These are the specifications for International model. Please note that this unit is different from Japanese domestic model.
※2 Angle (displacement) scale is necessary to valid this function.
※3 USB flash drive is not included.

Model	Capacity	Display
DTXS-0.5N-Z(※1)	0.5N-m (50N-cm)	0.500N-m (50.00N-cm)
DTXS-2N	2 N-m (200N-cm)	2.000N-m (200.0N-cm)
DTXS-5N	5 N-m (500N-cm)	5.000N-m (500.0N-cm)
DTXS-10N	10N-m (1000N-cm)	10.00N-m (1000N-cm)
DTXA-0.5N-Z(※1)	0.5N-m (50N-cm)	0.500N-m (50.00N-cm)
DTXA-2N	2 N-m (200N-cm)	2.000N-m (200.0N-cm)
DTXA-5N	5 N-m (500N-cm)	5.000N-m (500.0N-cm)
DTXA-10N	10N-m (1000N-cm)	10.00N-m (1000N-cm)

※1 The Unit shown in only "N-cm"
※1 The Table and the Pins sold separately.
※ The above model except DTXS-0.5N-Z and DTXA-0.5N-Z are models with a standard table and standard pins. DTXS-0.5N-Z and DTXA-0.5N-Z are models with a standard table and standard pins.