

Digital force gauges

RZE series



The RZE series is a new customer-friendly model that follows the functionality of conventional digital push-pull gauges but greatly improves operability.

They come with such convenient functions as data output by use of a newly adopted USB and charging and they also feature quick and easy operations such as changing sampling rates, 3 units, printer output and display reversing.

This digital force gauge goes beyond conventional thinking, with a shape that fits your hand and operation buttons.

Standard Accessories



Standard Specifications

Measurement unit	N, Kgf, lb selectable
Accuracy	Within $\pm 0.2\%$ of rated capacity
Allowable overload	120% of rated capacity (Overload alarm at about 110%)
Measurement system	Track mode/Peak hold mode/ Compression-tension peak hold mode selectable
Indication update cycle	1, 2, 5, 10, 20 times/sec. selectable
Sampling cycle	1ms, 5ms, 16ms, 50ms, 125ms, 250ms selectable
Communication output	USB
Analog output	$\pm 2V/F.S.$
Printer output	SANEI thermal printer, MITSUTOYO DIGIMATIC output
Operating temperature range	0 to $+40^{\circ}\text{C}$
Guaranteed temperature range	$+5$ to $+40^{\circ}\text{C}$
Continuous operation time	30 hours after full charge
Power supply	Dedicated nickel-metal hydride battery Dedicated AC adaptor: MODEL-780 (100 to 240VAC) Dedicated USB cable: MODEL-RZ-USB
Dimensions	W68 x D40 x H232mm
Weight	Approx. 375g

Model List

MODEL	RZE-1	RZE-2	RZE-5	RZE-10	RZE-20	RZE-50	RZE-100
Capacity	10N (1kgf)	20N (2kgf)	50N (5kgf)	100N (10kgf)	200N (20kgf)	500N (50kgf)	1000N (100kgf)
Indication range	0.001-10.000N (0.1gf-1.0000kgf)	0.01-20.00N (1gf-2.000kgf)	0.01-50.00N (1gf-5.000kgf)	0.01-100.00N (1gf-10.000kgf)	0.1-200.0N (10gf-20.00kgf)	0.1-500.0N (10gf-50.00kgf)	0.1-1000.0N (10gf-100.00kgf)
Minimum display unit	0.001N (0.1gf)	0.01N (1gf)			0.1N (10gf)		

Optional cables (Dedicated for RZE series)

RZE-OP-1	I/O cable
RZE-OP-2	I/O cable
RZE-OP-3	Cable for printer DP-1VR MITSUTOYO made
RZE-OP-4	Cable for line thermal printer Sanei Electric

If you only want stand control, please purchase RZE-OP-1.
If you wish to have comparator output or analog output in addition to the above functions, please purchase RZE-OP-2.

RZ-3000 (Dedicated software for RZE series)



Software for Excel



Real-time waveform

This is dedicated software designed to store data acquired by the RZE Series on a PC. It acquires and sends real-time data to a PC to show waveform graphs and maximum values. Measurement data can be output in CSV files and output CSV files can be opened using Excel. The standard interface is the USB interface. (The USB cable is included with the RZE force gauge as a standard accessory.)

Recommended Environment

Microsoft Windows 7,8,10,11 Japanese or English version
Memory: 2GB or more
CD-ROM drive x 1 (when installing this software)