



Mikrosize®

TOUCH SCREEN ROCKWELL HARDNESS TESTER



Lifting Screw



Lifting Screw



Indenter Fixed



Load Cell System



Testing Interface



The testing interface will automatically match the corresponding test force and the selected indenter. The in-time test force curve will be shown on coordinate axis(X-axis:Time,Y-axis:Force)

Scale	Test Force(N)	Indenter
HRA	588.4(60kg)	Diamond
HRB	980.7(100kg)	Ball
HRC	1471(150kg)	Diamond

Operation Interface



1. Setting Interface
2. Testing Interface
3. Display Interface
4. Diagram Interface
5. Program Setting Interface

Selecting Interface



Model	iRocky-150CL
Test Force	98.07N(10kg), $\pm 2.0\%$
Total Test Force	60kgf (588.4N), 100kgf (980.7N), 150kgf (1471N) ; $\pm 1.0\%$
Indenter Specification	Diamond Rockwell Indenter, $\Phi 1.5875\text{mm}$ Ball Indenter
Test Range	20-95HRA, 10-100HRB, 10-70HRC
Hardness Display	8" Touch screen (Option : Computer)
Hardness Resolution	0.1HR
Hardness Scale	HRA, HRD, HRC, HRFW, HRBW, HRHW, HREW, HRKW, HRL, HRM, HRP, HRR, HRS, HRV
Data Output	Touch Screen / Portable Printer / RS232
Loading Method	Initial Test Force : Manual Loading Main Test Force : Auto Loading, Dwelling, Unloading
Power Supply	AC110V/220V $\pm 5\%$, 50-60Hz
Dwelling Time	2-60s Adjustable
Test Height	230 mm / Test Throat : 170mm
Machine Dimension	475x200x700mm (LxWxH)
Net Weight	70 kg.



Rockwell Hardness Block



Gradienter



Diamond Indenter



Power Adaptor



$\Phi 1.5875\text{mm}$ Ball Indenter



Level Adjusting Feet



Test Anvil



Portable Printer



CERTIFICATE ISO/IEC 17025



บริการติดตั้ง สอนการใช้งาน



รับประกัน 1 ปี (ภายใต้การใช้งาน)