



Mikrosize®

Programmable Temperature And Humidity Test Chamber



Outer Shell Material

- Cold-rolled steel plate with paint baking

Thermal Insulation Material

- High-temperature resistant high-density polyurethane foam insulation material

System Air Circulation Mode

- Centrifugal fan - wide-band forced air circulation (top-out and bottom-in)

Refrigerator

- Hermetic piston-type France Tecumseh compressor or American Emerson scroll compressor

Power Supply

- 220V AC $\pm 10\%$ 50Hz or 380V AC $\pm 10\%$ 50Hz

Refrigerant

- R404A American Honeywell environmental protection refrigerant (R23+R404)

Condensation Mode

- Air-cooled

Heater

- Nickel-chromium alloy heating wire heater

Humidifier

- Semi-hermetic steam humidification

Water Supply Mode

- Automatic circulating water supply

Water Supply Mode

- No-fuse switch, (compressor overload, refrigerant high and low pressure, over-humidity and over-temperature) protection switch, fuse fault warning system

Model	THT-80	THT-225	THT-408	THT-1000
Inner Chamber Volume	80L	225L	408L	1000L
Inner Chamber Size W*H*D (mm)	400x500x400	500x750x600	600x850x800	1000x1000x1000
Outer Chamber Size W*H*D (mm)	930x1450x950	1070x1610x1170	1170x1710x1270	1550x1650x1470
Temperature and Humidity Control Range	Temperature: -40°C~150°C/-70°C~150°C Humidity: 20%~98%RH (other temperature and humidity specifications can be customized)			
Temperature and Humidity Fluctuation	$\pm 0.5^{\circ}\text{C}$; $\pm 2\%\text{RH}$			
Temperature and Humidity Deviation	Temperature: $\pm 0.5^{\circ}\text{C}$ ~ $\pm 2^{\circ}\text{C}$; Humidity: $\pm 3\%\text{RH}$ ($> 75\%\text{RH}$) $\pm 5\%\text{RH}$ ($\leq 75\%\text{RH}$)			
Temperature and Humidity Uniformity	$\leq 2^{\circ}\text{C}$; $\pm 3\%\text{RH}$			
Heating Rate	About $3^{\circ}\text{C}/\text{min}$ (non-linear, no load)			
Cooling Rate	Average $1^{\circ}\text{C}/\text{min}$ (non-linear, no load)			
Controller Resolution	$\pm 0.3^{\circ}\text{C}$; $\pm 2.5\%\text{RH}$			
Inner Wall Material	SUS304# stainless steel plate			