



Mikrosize®

Single Column Electronic Universal Testing Machine



บริการติดตั้ง สอนการใช้งาน



รับประกัน 1 ปี (ภายใต้การใช้งาน)

Model		UTMTSC5	UTMTSC100	UTMTSC1000
Capacity	KN	0.05	1	10
	KG	5	100	1000
	lb	11	220	2240
Unit Switching		G,Kg,Lb,N,KN		
Displacement Unit Switching		Inch/cm/mm		
Effective Force Measurement Range		0.4%~100%FS		
Force Accuracy		Within $\pm 1\%$ of The Indicated Value		
Force Value Resolution		1/300000		
Displacement Accuracy		Within $\pm 1\%$ of The Indicated Value		
Deformation Measuring Range		2%~100%FS		
Precision of Deformation Indication		Within $\pm 1\%$ of The Indicated Value		
Large Deformation Indication Error		Within $\pm 1\%$ of The Indicated Value		
Maximum Test Speed		500mm/min;The Maximum Value is 1000mm/min(Optional)		
Minimum Test Speed		0.1mm/min		
Speed Accuracy		Within $\pm 1\%$ of The Indicated Value		
Crossbeam Stroke		No - fixture test stroke: 920mm		
Fixture Configuration		Configured according to customer requirements		
Return Mode		Manual, Automatic		
Stop Method		1. Automatically stop at the maximum fracture value 2. Stop when the upper and lower limit safety settings are reached		
Safety Device		1. Mechanical travel switch protection 2. Emergency stop switch for emergency braking		
Overload Protection		When reaching 100% of the maximum load, the machine automatically stops for protection		
Power Supply		220V.AC/50Hz (Can be selected as 110V.AC/60Hz according to the country)		
Machine Size/Weight		L*W*H:500mm*350mm*1160mm About 50kg		