

diff(1) — Linux manual page

[NAME](#) | [SYNOPSIS](#) | [DESCRIPTION](#) | [AUTHOR](#) | [REPORTING BUGS](#) | [COPYRIGHT](#) | [SEE ALSO](#) | [COLOPHON](#)

 DIFF(1)

User Commands

DIFF(1)

NAME [top](#)

diff – compare files line by line

SYNOPSIS [top](#)

diff [*OPTION*]... *FILES*

DESCRIPTION [top](#)

Compare *FILES* line by line.

Mandatory arguments to long options are mandatory for short options too.

- normal**
output a normal diff (the default)
- q, --brief**
report only whether files differ
- s, --report-identical-files**
also report if two files are the same
- c, -C NUM, --context[=*NUM*]**
output NUM (default 3) lines of copied context
- u, -U NUM, --unified[=*NUM*]**
output NUM (default 3) lines of unified context
- e, --ed**
output an ed script
- n, --rcs**
output an RCS format diff
- y, --side-by-side**
output in two columns

-W, --width=NUM
output at most NUM (default 130) print columns

--left-column
output only the left column of common lines

--suppress-common-lines
do not output common lines

-p, --show-c-function
show which C function each change is in

-F, --show-function-line=RE
show the most recent line matching RE

--label LABEL
use LABEL instead of file name and timestamp (can be repeated)

-t, --expand-tabs
expand tabs to spaces in output

-T, --initial-tab
make tabs line up by prepending a tab

--tabsize=NUM
tab stops every NUM (default 8) print columns

--suppress-blank-empty
suppress space or tab before empty output lines

-l, --paginate
pass output through 'pr' to paginate it

-r, --recursive
recursively compare any subdirectories found

--no-dereference
don't follow symbolic links

-N, --new-file
treat absent files as empty

--unidirectional-new-file
treat absent first files as empty

--ignore-file-name-case
ignore case when comparing file names

--no-ignore-file-name-case
consider case when comparing file names

-x, --exclude=PAT
exclude files that match PAT

-X, --exclude-from=FILE
exclude files that match any pattern in FILE

-S, --starting-file=FILE

start with FILE when comparing directories

--from-file=FILE1
compare FILE1 to all operands; FILE1 can be a directory

--to-file=FILE2
compare all operands to FILE2; FILE2 can be a directory

-i, --ignore-case
ignore case differences in file contents

-E, --ignore-tab-expansion
ignore changes due to tab expansion

-Z, --ignore-trailing-space
ignore white space at line end

-b, --ignore-space-change
ignore changes in the amount of white space

-w, --ignore-all-space
ignore all white space

-B, --ignore-blank-lines
ignore changes where lines are all blank

-I, --ignore-matching-lines=RE
ignore changes where all lines match RE

-a, --text
treat all files as text

--strip-trailing-cr
strip trailing carriage return on input

-D, --ifdef=NAME
output merged file with '#ifdef NAME' diffs

--GTYPE-group-format=GFMT
format GTYPE input groups with GFMT

--line-format=LFMT
format all input lines with LFMT

--LTYPE-line-format=LFMT
format LTYPE input lines with LFMT

These format options provide fine-grained control over the output

of diff, generalizing **-D/--ifdef**.

LTYPE is 'old', 'new', or 'unchanged'.
GTYPE is LTYPE or 'changed'.

GFMT (only) may contain:

%< lines from FILE1

%> lines from FILE2

%= lines common to FILE1 and FILE2

%[-][WIDTH][.[PREC]]{doxX}LETTER
printf-style spec for LETTER

LETTERS are as follows for new group, lower case for old group:

F first line number

L last line number

N number of lines = L-F+1

E F-1

M L+1

%(A=B?T:E)
if A equals B then T else E

LFMT (only) may contain:

%L contents of line

%l contents of line, excluding any trailing newline

%[-][WIDTH][.[PREC]]{doxX}n
printf-style spec for input line number

Both GFMT and LFMT may contain:

%% %

%c'C' the single character C

%c'W000'
the character with octal code 000

C the character C (other characters represent themselves)

-d, --minimal
try hard to find a smaller set of changes

--horizon-lines=NUM
keep NUM lines of the common prefix and suffix

--speed-large-files
assume large files and many scattered small changes

--color[=WHEN]
color output; WHEN is 'never', 'always', or 'auto'; plain
--color means **--color='auto'**

--palette=PALETTE
the colors to use when **--color** is active; PALETTE is a
colon-separated list of terminfo capabilities

`--help` display this help and exit

`-v, --version`
output version information and exit

FILES are 'FILE1 FILE2' or 'DIR1 DIR2' or 'DIR FILE' or 'FILE DIR'. If `--from-file` or `--to-file` is given, there are no restrictions on FILE(s). If a FILE is '-', read standard input. Exit status is 0 if inputs are the same, 1 if different, 2 if trouble.

AUTHOR [top](#)

Written by Paul Eggert, Mike Haertel, David Hayes, Richard Stallman, and Len Tower.

REPORTING BUGS [top](#)

Report bugs to: bug-diffutils@gnu.org
GNU diffutils home page: <<https://www.gnu.org/software/diffutils/>>
General help using GNU software: <<https://www.gnu.org/gethelp/>>

COPYRIGHT [top](#)

Copyright © 2026 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>. This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO [top](#)

`wdiff(1)`, [cmp\(1\)](#), [diff3\(1\)](#), [sdiff\(1\)](#), [patch\(1\)](#)

The full documentation for `diff` is maintained as a Texinfo manual. If the `info` and `diff` programs are properly installed at your site, the command

`info diff`

should give you access to the complete manual.

COLOPHON [top](#)

This page is part of the *diffutils* (GNU diff utilities) project. Information about the project can be found at <http://savannah.gnu.org/projects/diffutils/>. If you have a bug report for this manual page, send it to bug-diffutils@gnu.org. This page was obtained from the project's upstream Git repository ([git://git.savannah.gnu.org/diffutils.git](https://git.savannah.gnu.org/diffutils.git)) on 2026-05-24. (At that time, the date of the most recent commit that was found in the repository was 2026-05-09.) If you discover any rendering problems in this HTML version of the page, or you believe there is

a better or more up-to-date source for the page, or you have corrections or improvements to the information in this COLOPHON (which is *not* part of the original manual page), send a mail to man-pages@man7.org

diffutils 3.12.26-bbc1

May 2026

DIFF(1)

Pages that refer to this page: [cmp\(1\)](#), [diff3\(1\)](#), [diffman-git\(1\)](#), [gendiff\(1\)](#), [git-config\(1\)](#), [git-diff\(1\)](#), [git-diff-files\(1\)](#), [git-diff-index\(1\)](#), [git-diff-pairs\(1\)](#), [git-diff-tree\(1\)](#), [grep\(1\)](#), [patch\(1\)](#), [quilt\(1\)](#), [sdiff\(1\)](#), [suffixes\(7\)](#)

HTML rendering created 2026-05-30 by [Michael Kerrisk](#), author of *The Linux Programming Interface*.

For details of in-depth **Linux/UNIX system programming training courses** that I teach, look [here](#).

Hosting by [jambit GmbH](#).

